Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Jameco Part Number 35561

The Undocumented Z80 Documented

Sean Young

Version 0.4, September 2001

Copyright Statement

Copyright ©1997, 1998, 2001 Sean Young.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1 or any later version published by the Free Software Foundation; with no Invariant Sections, with no Front-Cover Texts, and with no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Contents

1 Introduction **1**
- 1.1 History . . . 1
- 1.2 Where to get this document . . . 1
- 1.3 Feedback . . . 1

2 Overview **2**
- 2.1 History of the Z80 . . . 2
- 2.2 Registers . . . 2
- 2.3 Flags . . . 3
- 2.4 Power on defaults . . . 4
- 2.5 Pin Descriptions [7] . . . 4

3 Undocumented Opcodes **7**
- 3.1 CB Prefix [5] . . . 7
- 3.2 DD Prefix [5] . . . 7
- 3.3 FD Prefix [5] . . . 8
- 3.4 ED Prefix [5] . . . 8
- 3.5 DDCB Prefix . . . 9
- 3.6 FDCB Prefixes . . . 11
- 3.7 Combinations of Prefixes . . . 11

4 Undocumented Instructions **12**
- 4.1 BIT instructions . . . 12
- 4.2 Memory Block Instructions [1] . . . 13
- 4.3 I/O Block Instructions . . . 13
- 4.4 16 bit I/O ports . . . 14
- 4.5 Block Instructions . . . 14
- 4.6 16 Bit Additions . . . 14
- 4.7 DAA Instruction . . . 14

5 Interrupts **16**
- 5.1 Non-Maskable Interrupts (NMI) . . . 16
- 5.2 Maskable Interrupts (INT) . . . 16
- 5.3 Things affecting the Interrupt flip-flops . . . 17
- 5.4 HALT instruction . . . 18
- 5.5 Where interrupts are accepted . . . 18

6 Timing and R register **20**
6.1 R register and memory refresh 20
6.2 Undocumented Timings 20

7 Other Information **22**
7.1 Errors in official documentation 22

8 Instruction Tables **24**
8.1 8-Bit Load Group 24
8.2 16-Bit Load Group 25
8.3 Exchange, Block Transfer, Block Search Group 27
8.4 8-Bit Arithmetic and Logical Group 28
8.5 General-Purpose Arithmetic and CPU Control Group 28
8.6 16-Bit Arithmetic Group 29
8.7 Rotate and Shift Group 30
8.8 Bit Set, Reset and Test Group 31
8.9 Jump Group 31
8.10 Call and Return Group 32
8.11 Input and Output Group 33

9 Instructions Sorted by Opcode **34**

10 GNU Free Documentation License **41**
10.1 Applicability and Definitions 41
10.2 Verbatim Copying 42
10.3 Copying in Quantity 43
10.4 Modifications 43
10.5 Combining Documents 45
10.6 Collections of Documents 45
10.7 Aggregation With Independent Works 46
10.8 Translation 46
10.9 Termination 46
10.10Future Revisions of This License 46

Chapter 1

Introduction

1.1 History

Ever since I first started writing an MSX emulator, I've been very interested in getting the emulation absolutely correct — including the undocumented features. Not only to make sure that all games work, but also to make sure that if a program crashes, it crashes exactly the same way if running on an emulator as on the real thing. Only then is perfection achieved.

I set about collecting information. I found pieces of information on the Internet, but not everything there is to know. So I tried to fill in the gaps, the results of which I put on my website. Various people have helped me since then; this is the result of all those efforts and to my knowledge this document covers more undocumented features than any other.

Previous documents I had written were in plain text and Microsoft Word, which I now find very embarrassing, so I decided to combine them all and use LaTeX. Apart from a full re-write, the only changed information is "Power on defaults" (section 2.4) and the algorithm for the CF and HF flags for `OTIR` and friends (section 4.3).

1.2 Where to get this document

The latest version is always available in LaTeX and pdf at the following location:

`http://www.msxnet.org/tech/`

1.3 Feedback

I welcome any kind of feedback. I would like to hear about any mistakes in this document or any additions you might have. Also note that there are a few flags which are still unknown, I would be most grateful if someone could figure them out (please include an instruction exerciser to show that your findings are correct).

You can reach me at `sean@msxnet.org` and my website can be found at `http://www.msxnet.org/`.

Chapter 2

Overview

2.1 History of the Z80

In 1969 Intel were approached by a Japanese company called Busicom to produce chips for Busicom's electronic desktop calculator. Intel suggested that the calculator should be built around a single-chip generalized computing engine and thus was born the first microprocessor — the 4004. Although it was based on ideas from much larger mainframe and mini-computers the 4004 was cut down to fit onto a 16-pin chip, the largest that was available at the time, so that its data bus and address bus were each only 4-bits wide.

Intel went on to improve the design and produced the 4040 (an improved 4-bit design) the 8008 (the first 8-bit microprocessor) and then in 1974 the 8080. This last one turned out to be a very useful and popular design and was used in the first home computer, the Altair 8800, and CP/M.

In 1975 Federico Faggin who had had worked at Intel on the 4004 and its successors left the company and joined forces with Masatoshi Shima to form Zilog. At their new company Faggin and Shima designed a microprocessor that was compatible with Intel's 8080 (it ran all 78 instructions of the 8080 in exactly the same way that Intel's chip did) but had many more abilities (an extra 120 instructions, many more registers, simplified connection to hardware). Thus was born the mighty Z80!

The original Z80 was first released in July 1976. Since then newer versions have appeared with exactly the same architecture but running at higher speeds. The original Z80 ran with a clock rate of 2.5MHz, the Z80A runs at 4MHz, the Z80B at 6MHz, and the Z80H at 8Mhz.

Many companies produced machines based around Zilog's improved chip during the 1970's and 80's and because the chip could run 8080 code without needing any changes to the code the perfect choice of operating system was CP/M.

2.2 Registers

The following accessable registers exist in the Z80.



Accumlator and Flags

General purpose registers

Index registers

Special purpose registers

Alternate general purpose registers

For interrupts, there are two interrupt flop-flops, IFF1 and IFF2, and the interrupt mode is remembered. See chapter 5. Also there is an internal register which is described in section 4.3.

2.3 Flags

The conventional way of denoting the flags is with one letter, 'C' for the carry flag for example. It could be confused with the C register, so I've chosen to use the 'CF' notation for flags. Also in previous things I've written I called the two undocumented flags 5 and 3, but now I've changed to the same notation used in MAME[1], which is YF and XF, respectively.

bit	7	6	5	4	3	2	1	0
flag	SF	ZF	YF	HF	XF	PF	NF	CF

SF flag Set if the 2-complement value is negative. It's simply a copy of the most significant bit.

ZF flag Set if the value is zero.

YF flag A copy of bit 5 of the result.

HF flag The half-carry of an addition/subtraction (from bit 3 to 4). Needed for BCD correction with `DAA`.

XF flag A copy of bit 3 of the result.

PF flag This flag can either be the parity of the result (PF), or the 2-compliment signed overflow (VF): set if 2-compliment value doesn't fit in the register.

NF flag Shows whether the last operation was an addition (0) or an subtraction (1). This information is needed for DAA.

CF flag The carry flag, set if there was a carry after the most significant bit.

[1] http://www.mame.net/

2.4 Power on defaults

Matt[2] has done some excellent research for this. He found that AF and SP are always set to FFFFh after a reset, and all other registers are undefined (different depending on how long the CPU has been powered off, different for different Z80 chips). Of course the PC should be set to 0 after a reset, and so should the IFF1 and IFF2 flags (otherwise strange things could happen). Also since the Z80 is 8080 compatible, interrupt mode is probably 0.

Probably the best way to simulate this in an emulator is set PC, IFF1, IFF2, IM to 0 and set all other registers to FFFFh.

2.5 Pin Descriptions [7]

This section is also relevant even if you don't do anything with hardware. Besides, it took me hours to draw this picture.



$A_{15} - A_0$ *Address bus* (output, active high, 3-state). This bus is used for accessing the memory and for I/O ports. During the refresh cycle the IR register is put on this bus.

$\overline{BUSACK}$ *Bus Acknowledge* (output, active low). Bus Acknowledge indicates to the requesting device that the CPU address bus, data bus, and control signals $\overline{MREQ}$, $\overline{IORQ}$, $\overline{RD}$ and $\overline{WR}$ have been entered into their high-impedance states. The external now control these lines.

$\overline{BUSREQ}$ *Bus Request* (input, active low). Bus Request has a higher priority than $\overline{NMI}$ and is always recognised at the end of the current machine cycle. $\overline{BUSREQ}$ forces the CPU address bus, data bus and control signals $\overline{MREQ}$,

[2] redflame@xmission.com

$\overline{\texttt{IORQ}}$, $\overline{\texttt{RD}}$ and $\overline{\texttt{WR}}$ to go to a high-empedance state so that other devices can control these lines. $\overline{\texttt{BUSREQ}}$ is normally wired-OR and requres an external pullup for these applications. Extended $\overline{\texttt{BUSREQ}}$ periods due to extensive DMA operations can prevent the CPU from refreshing dynamic RAMs.

$\texttt{D}_7 - \texttt{D}_0$ *Data Bus* (input/output, active low, 3-state). Used for data exchanges with memory, I/O and interrupts.

$\overline{\texttt{HALT}}$ *Halt State* (output, active low). Indicates that the CPU has executed a `HALT` instruction and is waiting for either a maskable or nonmaskable interrupt (with the mask enabled) before operation can resume. While halted, the CPU stops increasing the PC so the instruction is re-executed, to maintain memory refresh.

$\overline{\texttt{INT}}$ *Interrupt Request* (input, active low). Interrupt Request is generated by I/O devices. The CPU honours a request at the end of the current instruction if IFF1 is set. $\overline{\texttt{INT}}$ is normally wired-OR and requires an external pullup for these applications.

$\overline{\texttt{IORQ}}$ *Input/Output Request* (output, active low, 3-state). Indicates that the address bus holds a vailid I/O address for an I/O read or write operation. $\overline{\texttt{IORQ}}$ is also generated concurrently with $\overline{\texttt{M1}}$ during an interrupt acknowledge cycle to indicate that an interrupt response vector can be placed on the databus.

$\overline{\texttt{M1}}$ *Machine Cycle One* (output, active low). $\overline{\texttt{M1}}$, together with $\overline{\texttt{MREQ}}$, indicates that the current machine cycle is the opcode fetch cycle of an instruction execution. $\overline{\texttt{M1}}$, together with $\overline{\texttt{IORQ}}$, indicates an interrupt acknowledge cycle.

$\overline{\texttt{MREQ}}$ *Memory Request* (output, active low, 3-state). Indicates that the address holds a valid address for a memory read or write cycle operations.

$\overline{\texttt{NMI}}$ *Non-Maskable Interrupt* (input, negative edge-triggered). $\overline{\texttt{NMI}}$ has a higher priority than $\overline{\texttt{INT}}$. $\overline{\texttt{NMI}}$ is always recognised at the end of the current instruction, independant of the status of the interrupt flip-flops and automatically forces the CPU to restart at location 0066h.

$\overline{\texttt{RD}}$ *Read* (output, active low, 3-state). Indicates that the CPU wants to read data from memory or an I/O device. The addressed I/O device or memory should use this signal to place data onto the data bus.

$\overline{\texttt{RESET}}$ *Reset* (input, active low). Initializes the CPU as follows: it resets the interrupt flip-flops, clears the PC and IR registes, and set the interrupt mode to 0. During reset time, the address bus and data bus go to a high-empedance state, and all control output signals go to the inactive state. Note that $\overline{\texttt{RESET}}$ must be active for a minimum of three full clock cycles before the reset operation is complete. Note that Matt found that SP and AF are set to FFFFh.

$\overline{\texttt{RFSH}}$ *Refresh* (output, active low). $\overline{\texttt{RFSH}}$, together with $\overline{\texttt{MREQ}}$, indicates that the IR registers are on the address bus (note that only the lower 7 bits are useful) and can be used for the refresh of dynamic memories.

$\overline{\texttt{WAIT}}$ *Wait* (input, active low). Indicates to the CPU axathat the addressed memory or I/O device are not ready for data transfer,x. The CPU continues to enter a wait state as long as this signal is active. Note that during this period memory is not refreshed.

$\overline{\texttt{WR}}$ *Write* (output, active low, 3-state). Indicates that the CPU wants to write data to memory or an I/O device. The addressed I/O device or memory should use this signal to store the data on the data bus.

Chapter 3

Undocumented Opcodes

There are quite a few undocumented opcodes/instructions. This section should describe every possible opcode (so you know what will be executed, whatever the value of the opcode is).

The following prefixes exist: CB, ED, DD, FD, DDCB and FDCB. Prefixes change the way the following opcodes are interpreted. All instructions without a prefix (not a value of one the above) are single byte opcodes, which are documented in the official documentation.

3.1 CB Prefix [5]

An opcode with a CB prefix is a rotate, shift or bit test/set/reset instruction. There are a few instructions missing from the official list, which are usually denoted with `SLL` (Shift Logical Left). It works like `SLA`, for one exception: it sets bit 0 (`SLA` resets it).

```
CB30    SLL B
CB31    SLL C
CB32    SLL D
CB33    SLL E
CB34    SLL H
CB35    SLL L
CB36    SLL (HL)
CB37    SLL A
```

3.2 DD Prefix [5]

In general, the instruction following the DD prefix is executed as is, but if the HL register is supposed to be used the IX register is used instead. Here are the rules:

- Any usage of HL is treated as an access to IX (except `EX DE,HL` and `EXX` and the ED prefixed instructions that use HL).

- Any access to (HL) is changed to (IX+d), where 'd' is a signed displacement byte placed after the main opcode — except `JP (HL)`, which isn't indirect anyway. The mnemonic should be `JP HL`.
- Any access to H is treated as an access to IXh (the high byte of IX) Except if (IX+d) is used as well.
- Any access to L is treated as an access to IXl (the low byte of IX) Except if (IX+d) is used aswell.
- A DD prefix before a CB selects a completely different instruction set, see Section 3.5.

Some examples:

Without DD prefix	With DD prefix
`LD H,(HL)`	`LD H,(IX+d)`
`LD H,A`	`LD IXh,A`
`LD L,H`	`LD IXl,IXh`
`JP (HL)`	`JP (IX)`
`LD DE,0`	`LD DE,0`
`LD HL,0`	`LD IX,0`

3.3 FD Prefix [5]

This prefix has the same effect as the DD prefix, though IY is used instead of IX. Note `LD IXl,IYh` is not possible: only IX or IY is accessed in one instruction.

3.4 ED Prefix [5]

There are a number of undocumented EDxx instructions, of which most are duplicates of documented instructions. Any instruction not listed has no effect (same behaviour as 2 `NOP` instructions).

The complete list except for the block instructions:

ED40	IN B,(C)	ED60	IN H,(C)
ED41	OUT (C),B	ED61	OUT (C),H
ED42	SBC HL,BC	ED62	SBC HL,HL
ED43	LD (nn),BC	ED63	LD (nn),HL
ED44	NEG	ED64	NEG**
ED45	RETN	ED65	RETN**
ED46	IM 0	ED66	IM 0**
ED47	LD I,A	ED67	RRD
ED48	IN C,(C)	ED68	IN L,(C)
ED49	OUT (C),C	ED69	OUT (C),L
ED4A	ADC HL,BC	ED6A	ADC HL,HL
ED4B	LD BC,(nn)	ED6B	LD HL,(nn)

**Undocumented instruction

```
ED4C  NEG**           ED6C  NEG**
ED4D  RETI            ED6D  RETN**
ED4E  IM 0**          ED6E  IM 0**
ED4F  LD R,A          ED6F  RLD

ED50  IN D,(C)        ED70  IN (C) / IN F,(C)**
ED51  OUT (C),D       ED71  OUT (C),0**
ED52  SBC HL,DE       ED72  SBC HL,SP
ED53  LD (nn),DE      ED73  LD (nn),SP
ED54  NEG**           ED74  NEG**
ED55  RETN**          ED75  RETN**
ED56  IM 1            ED76  IM 1**
ED57  LD A,I          ED77  NOP**
ED58  IN E,(C)        ED78  IN A,(C)
ED59  OUT (C),E       ED79  OUT (C),A
ED5A  ADC HL,DE       ED7A  ADC HL,SP
ED5B  LD DE,(nn)      ED7B  LD SP,(nn)
ED5C  NEG**           ED7C  NEG**
ED5D  RETN**          ED7D  RETN**
ED5E  IM 2            ED7E  IM 2**
ED5F  LD A,R          ED7F  NOP**
```

The ED70 instruction reads from I/O port C, but does not store the result. It just affects the flags like the other `IN x,(C)` instruction. ED71 simply outs the value 0 to I/O port C.

The ED63 is a duplicate of the 22 opcode (`LD (nn),HL`) and similarly ED6B is a duplicate of the 2A opcode. Of course the timings are different. These instructions are listed in the official documentation.

According to Gerton Lunter[1]:

> The instructions ED 4E and ED 6E are `IM 0` equivalents: when FF was put on the bus (physically) at interrupt time, the Spectrum continued to execute normally, whereas when an EF (`RST 28h`) was put on the bus it crashed, just as it does in that case when the Z80 is in the official interrupt mode 0. In `IM 1` the Z80 just executes a `RST 38h` (opcode FF) no matter what is on the bus.

All the `RETI/RETN` instructions are the same, all like the `RETN` instruction. So they all, including `RETI`, copy IFF2 to IFF1. More information on `RETI` and `RETN` and `IM x` is in section 5.3.

3.5 DDCB Prefix

The undocumented DDCB instructions store the result (if any) of the operation in one of the seven all-purpose registers, which one depends on the lower 3 bits of the last byte of the opcode (not operand, so not the offset).

[1] gerton@math.rug.nl

000 B
001 C
010 D
011 E
100 H
101 L
110 (none: documented opcode)
111 A

The documented DDCB0106 is `RLC (IX+01h)`. So, clear the lower three bits (DDCB0100) and something is done to register B. The result of the RLC (which is stored in (IX+01h)) is now also stored in register B. Effectively, it does the following:

```
LD B,(IX+01h)
RLC B
LD (IX+01h),B
```

So you get double value for money. The result is stored in B and (IX+01h). The most common notation is: `RLC (IX+01h),B`

I've once seen this notation:

```
RLC (IX+01h)
LD B,(IX+01h)
```

That's not correct: B contains the rotated value, even if (IX+01h) points to ROM. The DDCB SET and RES instructions do the same thing as the shift/rotate instructions:

```
DDCB10C0    SET 0,(IX+10h),B
DDCB10C1    SET 0,(IX+10h),C
DDCB10C2    SET 0,(IX+10h),D
DDCB10C3    SET 0,(IX+10h),E
DDCB10C4    SET 0,(IX+10h),H
DDCB10C5    SET 0,(IX+10h),L
DDCB10C6    SET 0,(IX+10h) - documented instruction
DDCB10C7    SET 0,(IX+10h),A
```

So for example with the last instruction, the value of (IX+10h) with bit 0 set is also stored in register A.

The DDCB BIT instructions do not store any value; they merely test a bit. That's why the undocumented DDCB BIT instructions are no different from the official ones:

```
DDCB d 78    BIT 7,(IX+d)
DDCB d 79    BIT 7,(IX+d)
DDCB d 7A    BIT 7,(IX+d)
DDCB d 7B    BIT 7,(IX+d)
DDCB d 7C    BIT 7,(IX+d)
DDCB d 7D    BIT 7,(IX+d)
DDCB d 7E    BIT 7,(IX+d) - documented instruction
DDCB d 7F    BIT 7,(IX+d)
```

3.6 FDCB Prefixes

Same as for the DDCB prefix, though IY is used instead of IX.

3.7 Combinations of Prefixes

This part may be of some interest to emulator coders. Here we define what happens if strange sequences of prefixes appear in the instruction cycle of the Z80.

If CB or ED is encountered, that byte plus the next make up an instruction. FD or DD should be seen as prefix setting a flag which says "use IX or IY in stead of HL", and not an instruction. In a large sequence of DD and FD bytes, it is the last one that counts. Also any other byte (or instruction) resets this flag.

```
FD DD 00 21 00 10    NOP NOP NOP LD HL,1000h
```

Chapter 4

Undocumented Instructions

4.1 BIT instructions

`BIT n,r` behaves much like `AND r,2`$^{\texttt{n}}$ with the result thrown away, and CF flag unaffected. So compare `BIT 7,A` with `AND 80h`: flag YF and XF are reset, SF is set if bit 7 was actually set; ZF is set if the result was 0 (bit was reset), and PF is effectively set if ZF is set (the result of the AND leaves either no bits set (PF reset) or one bit set (PF set). So the rules for the flags are:

SF flag Set if n = 7 and tested bit is set.

ZF flag Set if the tested bit is reset.

YF flag Set if n = 5 and tested bit is set.

HF flag Always set.

XF flag Set if n = 3 and tested bit is set.

PF flag Set just like ZF flag.

NF flag Always reset.

CF flag Unchanged.

This is were things start to get strange. With the `BIT n,(IX+d)` instructions, the flags behave just like the `BIT n,r` instruction, except for YF and XF. These are not copied from the result but from something completely different, namely bit 5 and 3 of the high byte of IX+d (so IX plus the displacement).

Things get more bizarre with the `BIT n,(HL)` instruction. Again, except for YF and XF the flags are the same. YF and XF are copied from some sort of internal register. This register is related to 16 bit additations. Most instructions do not change this register. Unfortunately, I haven't tested all instructions yet, but here is the list so far.

`ADD HL,xx` Use the high byte of HL, ie. H before the addition.

`LD r,(IX+d)` Use high byte of the resulting address IX+d.

`JR d` Use high byte target address of the jump.

LD r,r' Doesn't change this register.

Any help here would be most appreciated!

4.2 Memory Block Instructions [1]

The `LDI/LDIR/LDD/LDDR` instructions affect the flags in a strange way. At every iteration, a byte is copied. Take that byte and add the value of register A to it. Call that value n. Now, the flags are:

YF flag A copy of bit 1 of n.

HF flag Always reset.

XF flag A copy of bit 3 of n.

PF flag Set if BC not 0.

SF, ZF, CF flags These flags are unchanged.

And now for `CPI/CPIR/CPD/CPDR`. This instruction compares a series of bytes in memory to register A. Effectively, it can be said it does `CP (HL)` at every iteration. The result of that compare sets the HF flag, which is important for the next step. Take the value of register A, substract the value of the memory address, and finally substract the value of HF flag, which is set or reset by the hypothetical `CP (HL)`. So, `n = A - (HL) - HF`.

SF, ZF, HF flags Set by the hypothetical `CP (HL)`.

YF flag A copy of bit 1 of n.

XF flag A copy of bit 3 of n.

PF flag Set if BC is not 0.

NF flag Always set.

CF flag Unchanged.

4.3 I/O Block Instructions

These are the most be bizarre instructions, as far as flags is concerned. The PF flag is still unclear[1], and the HF and CF are most strange. The out instructions behave differently than the in instructions, which doesn't make the CPU very symmetrical.

First for the `OUTI/OTIR/OUTD/OTDR` instructions. At every iteration, a byte is read from memory and sent to an I/O port. Take that value (call it n), and add register L to it, *after* the HL register is increased (`OUTI` and `OTIR`) or decreased (`OUTD` and `OTDR`). If that calculation makes a carry (ie. it's larger than 255), both CF and HF are set. Otherwise CF and HF are reset.

[1] Help would be most appreciated.

SF, ZF, YF, XF flags Affected by decreasing register B, as in `DEC B`.

CF, HF flags Set if (L + n) > 255.

NF flags A copy of bit 7 of n.

PF flag This flag is a mystery. It seems it is dependant on bits 2,1,0 of register C, bits 2,1,0 of n and register B.

The `INI/INIR/IND/INDR` instructions are slightly different. The value of CF and HF are computed differently. Call the value that is read from the I/O port n. Take the value of register C, and in the the case of `INIR` and `INI`, increase it by 1 and in the case of `INDR` and `IND`, decrease it by 1. Keep the result 8 bits — so it will be 0 if n was 255, with `INI`. Now add n to this; if it's larger than 255, set the CF and HF flags. Apart from that, the flags are the same.

4.4 16 bit I/O ports

Officially the Z80 has an 8 bit I/O port address space. When using the I/O ports, the 16 address lines are used. And in fact, the high 8 bit do actually have some value, so you can use 65536 ports after all. `IN r,(C)`, `OUT (C),r`, and the Block I/O instructions actually place the entire BC register on the address bus. Similary `IN A,(n)` and `OUT (n),A` put A × 256 + n on the address bus.

4.5 Block Instructions

The repeated block instructions simply decrease the PC by two so the instruction is simply re-executed. So interrupts can occur during block instructions. So, `LDIR` is simply `LDI` + if BC is not 0, decrease PC by 2.

4.6 16 Bit Additions

The 16 bit additions are a bit more complicated. 16 bit additions are done in two stages: first the lower bytes are added, then the two higher bytes. The SF, YF, HF, XF flags are affected as by the second (high) 8 bit addition. ZF is set if the whole 16 bit result is 0.

4.7 DAA Instruction

This instruction is useful when you're using BCD values. After an addition or subtraction, `DAA` corrects the value back to BCD again. Note that it uses the CF flag, so it cannot be used after `INC` and `DEC`.

Here is the correction table, copied from the "Mostek Z80 Programming Manual". This table is all I know about `DAA` operation.

NF	CF	high nibble	HF	low nibble	# added to A	CF after execution
0	0	0-9	0	0-9	00	0
0	0	0-8	0	a-f	06	0
0	0	0-9	1	0-3	06	0
0	0	a-f	0	0-9	60	1
0	0	9-f	0	a-f	66	1
0	0	a-f	1	0-3	66	1
0	1	0-2	0	0-9	60	1
0	1	0-2	0	a-f	66	1
0	1	0-3	1	0-3	66	1
1	0	0-9	0	0-9	00	0
1	0	0-8	1	6-f	fa	0
1	1	7-f	0	0-9	a0	1
1	1	6-f	1	6-f	9a	1

Emulator builders: this instruction is hard to emulate. The Intel 80x86 equivalents are more or less the same, but differ for some input values. The best way to correctly emulate this instruction is by putting all possible output values (for A and F registers) in a table. The output depends on the following inputs: A register and HF, NF, CF flags. That's 11 bits in total, so the table will have size: $2^{11} \times 2 = 4096$ bytes, which isn't too bad.

Chapter 5

Interrupts

There are two types of interrupts, maskable and non-maskable. The maskable type is ignored if IFF1 is reset. Non-maskable interrupts (NMI) will are always accepted, and they have a higher priority, so if the two are requested at the same time the NMI will be accepted first.

For the interrupts, the following things are important: Interrupt Mode (set with the `IM 0, IM 1, IM 2` instructions), the interrupt flip-flops (IFF1 and IFF2), and the I register. When a maskable interrupt is accepted, a external device can put a value on the databus.

5.1 Non-Maskable Interrupts (NMI)

When a NMI is accepted, IFF1 is reset. At the end of the routine, IFF1 must be restored (so the running program is not affected). That's why IFF2 is there; to keep a copy of IFF1.

An NMI is accepted when the NMI pin on the Z80 is made low. The Z80 responds to the *change* of the line from +5 to 0 — so the interrupt line doesn't have a state, it's just a pulse. When this happens, a call is done to address 0066h and IFF1 is reset so the routine isn't bothered by maskable interrupts. The routine should end with an `RETN` (RETurn from Nmi) which is just a usual RET, but also copies IFF2 to IFF1, so the IFFs are the same as before the interrupt.

You can check whether interrupts were disabled or not during an NMI by using the `LD A,I` or `LD A,R` instruction. These instructions copy IFF2 to the PF flag.

5.2 Maskable Interrupts (INT)

If the INT line is low and IFF1 is set, a maskable interrupt is accepted — whether or not the the last INT routine has finished. That's why you should not enable interrupts during such a routine, and make sure that the device that generated it has put the INT line up again before ending the routine. So unlike NMI interrupts, the interrupt line has a state; it's not a pulse.

When an INT is accepted, both IFF1 and IFF2 are cleared, preventing another interrupt from occurring which would end up as an infinite loop (and

overflowing the stack). What happens next depends on the Interrupt Mode.

A device can place a value on the databus when the interrupt is accepted. Some computer systems do not utilize this feature, and this value ends up being FFh.

Interrupt Mode 0 This is the 8080 compatibility mode. The instruction on the bus is executed (usually an `RST #` instruction, but it can be anything. The I register is not used.

Interrupt Mode 1 An RST 38h is executed, no matter what value is put on the bus or what value the I register has.

Interrupt Mode 2 A call is made to the address read from memory. What address is read from is calculated as follows: (I register) × 256 + (value on bus). Of course a word (two bytes) are read, making the a address where the call is made to. In this way, you can have a vector table for interrupts.

At the end of a maskable interrupt, the interrupts should be enabled again. You can assume that was the state of the IFFs because otherwise the interrupt wasn't accepted. So, an INT routine always ends with an `EI` and a `RET` (`RETI` according to the official documentation, more about that later):

```
INT:
    .
    .
    .
    EI
    RETI or RET
```

Note a fact about `EI`: a maskable interrupt isn't accepted directly after it, so the next opportunity for an interrupt is after the `RETI`. This is very useful; if the INT line is still low, an interrupt is accepted again. If this happens a lot and the interrupt is generated before the `RETI`, the stack could overflow (since the routine would be called again and again). But this property of `EI` prevents this.

`DI` is not necessary at the start of the interrupt routine: the interrupt flip-flops are cleared when accepting the interrupt.

You can use `RET` instead of `RETI`, depending on the hardware setup. `RETI` is only useful if you have something like a Z80 PIO to support daisy-chaining: queueing interrupts. The PIO can detect that the routine has ended by the opcode of `RETI`, and let another device generate an interrupt. That is why I called all the undocumented EDxx RET instructions `RETN`: All of them operate alike, the only difference of `RETI` is its specific opcode which the Z80 PIO recognises.

5.3 Things affecting the Interrupt flip-flops

All the IFF related things are:

	IFF1	IFF2
CPU reset	0	0

DI	0	0	
EI	1	1	
Accept INT	0	0	
Accept NMI	0	-	
RETI/N	IFF2	-	All the EDxx RETI/N instructions
LD A,I/LD A,R	-	-	Copies IFF2 into PF flag

If you're working with a Z80 system without NMIs (like the MSX), you can forget all about the two separate IFFs; since a NMI isn't ever generated, the two will always be the same.

Some documenation says that when an NMI is accepted, IFF1 is first copied into IFF2 before IFF1 is cleared. If this is true, the state of IFF2 is lost after a nested NMI, which is undesirable. Have tested this in the following way: make sure the Z80 is in EI mode, generate an NMI. In the NMI routine, wait for another NMI before executing RETN. In the second NMI IFF2 was still set, so IFF1 is *not* copied to IFF2 when accepting an NMI.

Another interesting fact is this. I was trying to figure out whether the undocumented ED RET instructions were RETN or RETI. I tested this by putting the machine in EI mode, wait for an NMI and end with one of the ED RET instructions. Then execute a HALT instruction. If IFF1 was not restored, the machine would hang but this did not happen with any of the instructions, including the documented RETI!

Since every INT routine must end with EI followed by RETI officially, It does not matter that RETI copies IFF2 into IFF1; both are set anyway.

5.4 HALT instruction

The HALT instruction halts the Z80; it does not increase the PC so that the instruction is re-executed, until a maskable or non-maskable interrupt is accepted. Only then does the Z80 increase the PC again and continues with the next instruction. During the HALT state, the HALT line is set. The PC is increased before the interrupt routine is called.

5.5 Where interrupts are accepted

During execution of instructions, interrupts won't be accepted. Only *between* instructions. This is also true for prefixed instructions.

Directly after an EI or DI instruction, interrupts aren't accepted. They're accepted again after the instruction after the EI (RET in the following example). So for example, look at this MSX2 routine that reads a scanline from the keyboard:

```
LD    C,A
DI
IN    A,(0AAh)
AND   0F0h
ADD   A,C
OUT   (0AAh),A
EI
```

```
    IN    A,(0A9h)
    RET
```

You can assume that there never is an interrupt after the `EI`, before the `IN A,(0A9h)` — which would be a problem because the MSX interrupt routine reads the keyboard too.

Using this feature of `EI`, it is possible to check whether it is true that interrupts are never accepted during instructions:

```
    DI
    make sure INT is active
    EI
    insert instruction to test
INT:
    store PC where INT was accepted
    RET
```

And yes, for all instructions, including the prefixed ones, interrupts are never accepted during an instruction. Only after the tested instruction. Remember that block instructions simply re-execute themselves (by decreasing the PC with 2) so an interrupt is accepted after each iteration.

Another predictable test is this: at the "insert instruction to test" insert a large sequence of `EI` instructions. Of course, during execution of the `EI` instructions, no interrupts are accepted.

But now for the interesting stuff. ED or CB make up instructions, so interrupts are accepted after them. But DD and FD are prefixes, which only slightly affects the next opcode. If you test a large sequence of DDs or FDs, the same happens as with the `EI` instruction: no interrupts are accepted during the execution of these sequences.

This makes sense, if you think of DD and FD as a prefix which set the "use IX instead of HL" or "use IY instead of HL" flag. If an interrupt was accepted after DD or FD, this flag information would be lost, and:

```
DD 21 00 00    LD IX,0
```

could be interpreted as a simple `LD HL,0` if the interrupt was after the last DD. Which never happens, so the implementation is correct. Although I haven't tested this, as I imagine the same holds for NMI interrupts.

Chapter 6

Timing and R register

6.1 R register and memory refresh

During every first machine cycle (beginning of an instruction or part of it — prefixes have their own M1 two), the memory refresh cycle is issued. The whole IR register is put on the address bus, and the RFSH pin is lowered. It unclear whether the Z80 increases the R register before or after putting IR on the bus.

The R register is increased at every first machine cycle (M1). Bit 7 of the register is never changed by this; only the lower 7 bits are included in the addition. So bit 7 stays the same, but it can be changed using the `LD R,A` instruction.

Instructions without a prefix increase R by one. Instructions with an ED, CB, DD, FD prefix, increase R by two, and so do the DDCBxxxx and FDCBxxxx instructions (weird enough). Just a stray DD or FD increases the R by one. `LD A,R` and `LD R,A` access the R register after it is increased (by the instruction itself).

Remember that the block instructions simply decrease the PC with two, so the instructions are re-executed. So LDIR increased R by BC times 2 (note that in the case of BC = 0, R is increased by 10000h times 2, effectively 0).

Accepting an maskable or non-maskable interrupt increases the R by one.

After a hardware reset, or after power on, the R register is reset to 0.

That should cover all there is to say about the R register. It is often used in programs for a random value, which is good but of course not truly random.

6.2 Undocumented Timings

1. Stray DD or FD: same as a NOP (increases R by one).
2. EDxx (not one of the list above or block instruction): Same as two NOPs. Increases R by 2.
3. Accepting interrupts (all one M1 and thus increase R by one): (T states)

   IM 0: 13 (assuming the instruction is a RST)
   IM 1: 13
   IM 2: 19

NMI : 11

Chapter 7

Other Information

7.1 Errors in official documentation

In some official Zilog documentation, the are some errors. Some don't have all of these mistakes, so your documentation may not be flawed but these are just things to look out for.

- The Flag affection summary table shows that `LDI/LDIR/LDD/LDDR` instructions leave the SF and ZF in an undefined state. This is not correct; the SF and ZF flags are unaffected (like the same documentation says).
- Similary, the same table shows that `CPI/CPIR/CPD/CPDR` leave the SF and HF flags in an undefined state. Not true, they are affected as defined elsewhere in the documentation.
- Also, the table says about `INI/OUTD`/etc "Z=0 if B <> 0 otherwise Z=0"; of course the latter should be Z=1.
- The `INI/INIR/IND/INDR/OUTI/OUTD/OTIR/OTDR` instructions do affect the CF flag (some official documentation says they leave it unaffected, important!) and the NF flag isn't always set but may also be reset (see above for exact operation).
- When an NMI is accepted, the IFF1 isn't copied to IFF2. Only IFF1 is reset.
- In the 8-bit Load Group, the last two bits of the second byte of the `LD r,(IX + d)` opcode should be 10 and not 01.
- In the 16-bit Arithmetic Group, bit 6 of the second byte of the `ADD IX, pp` opcode should be 0, not 1.
- `IN x,(C)` resets the HF flag, it never sets it. Some documentation states it is set according to the result of the operation; this is impossible since no arithmetic is done in this instruction.

Bibliography

[1] Mark Rison Z80 page for !CPC.
`http://www.acorn.co.uk/ mrison/en/cpc/tech.html`

[2] YAZE (Yet Another Z80 Emulator). This is a CPM emulator by Frank Cringle. It emulates almost every undocumented flag, very good emulator. Also includes a very good instruction exerciser, and is released under the GPL.
`ftp://ftp.ping.de/pub/misc/emulators/yaze-1.10.tar.gz`

[3] Z80 Family Official Support Page by Thomas Scherrer. Very good – your one-stop Z80 page.
`http://www.geocities.com/SiliconValley/Peaks/3938/z80_home.htm`

[4] Spectrum FAQ technical information.
`http://www.void.jump.org/faq/tech_z80.html`

[5] Gerton Lunter's Spectrum emulator (Z80). In the package there is a file TECHINFO.DOC, which contains a lot of interesting information. Note that the current version can only be unpacked in Windows.
`ftp://ftp.void.jump.org/pub/sinclair/emulators/pc/dos/z80-400.zip`

[6] Mostek Z80 Programming Manual – a very good reference to the Z80.

[7] Z80 Product Specification, from MSX2 Hardware Information.
`http://www.hardwareinfo.msx2.com/pdf/Zilog/z80.pdf`

Chapter 8

Instruction Tables

8.1 8-Bit Load Group

Mnemonic	Symbolic Operation	Flags SF	ZF	YF	HF	XF	PF	NF	CF	Opcode 76 543 210	Hex	Bytes	M Cycles	T States	Comments
LD r,r'	r←r'	•	•	•	•	•	•	•	•	01 r r'		1	1	4	r,r' Reg
LD p,p'	p←p'	•	•	•	•	•	•	•	•	11 011 101	DD	2	2	8	000 B
										01 p p'					001 C
LD q,q'	q←q'	•	•	•	•	•	•	•	•	11 111 101	FD	2	2	8	010 D
										01 q q'					011 E
LD r,n	r←n	•	•	•	•	•	•	•	•	00 r 110		2	2	7	100 H
										← n →					101 L
LD p,n	p←n	•	•	•	•	•	•	•	•	11 011 101	DD	3	3	11	111 A
										00 p 110					
										← n →					
LD q,n	q←n	•	•	•	•	•	•	•	•	11 111 101	FD	3	3	11	p,p' Reg
										00 q 110					000 B
										← n →					001 C
LD r,(HL)	r←(HL)	•	•	•	•	•	•	•	•	01 r 110		1	2	7	010 D
LD r,(IX+d)	r←(IX+d)	•	•	•	•	•	•	•	•	11 011 101	DD	3	5	19	011 E
										01 r 110					100 IXh
										← d →					101 IXh
LD r,(IY+d)	r←(IY+d)	•	•	•	•	•	•	•	•	11 111 101	FD	3	5	19	111 A
										01 r 110					
										← d →					
LD (HL),r	(HL)←r	•	•	•	•	•	•	•	•	01 110 r		1	2	7	q,q' Reg
LD (IX+d),r	(IX+d)←r	•	•	•	•	•	•	•	•	11 011 101	DD	3	5	19	000 B
										01 110 r					001 C
										← d →					010 D
LD (IY+d),r	(IY+d)←r	•	•	•	•	•	•	•	•	11 111 101	FD	3	5	19	011 E
										01 110 r					100 IYl
										← d →					101 IYh
LD (HL),n	(HL)←n	•	•	•	•	•	•	•	•	00 110 110	36	2	3	10	111 A
										← n →					
LD (IX+d),n	(IX+d)←n	•	•	•	•	•	•	•	•	11 011 101	DD	4	5	19	
										01 110 110	36				
										← d →					
										← n →					
LD (IY+d),n	(IY+d)←n	•	•	•	•	•	•	•	•	11 111 101	FD	4	5	19	
										01 110 110	36				
										← d →					
										← n →					
LD A,(BC)	A←(BC)	•	•	•	•	•	•	•	•	00 001 010	0A	1	2	7	
LD A,(DE)	A←(DE)	•	•	•	•	•	•	•	•	00 011 010	1A	1	2	7	
LD A,(nn)	A←(nn)	•	•	•	•	•	•	•	•	00 111 010	3A	3	4	13	
										← n →					
										← n →					

(continued)

Mnemonic	Symbolic Operation	SF	ZF	YF	HF	XF	PF	NF	CF	Opcode 76 543 210	Hex	Bytes	M Cycles	T States	Comments
LD (BC),A	(BC)←A	•	•	•	•	•	•	•	•	00 000 010	02	1	2	7	
LD (DE),A	(DE)←A	•	•	•	•	•	•	•	•	00 010 010	12	1	2	7	
LD (nn),A	(nn)←A	•	•	•	•	•	•	•	•	00 110 010	32	3	4	13	
										← n →					
										← n →					
LD A,I	A←I	↕	↕	↕	0	↕	IFF2	0	•	11 101 101	ED	2	2	9	
										01 010 111	57				
LD A,R	A←R	↕	↕	↕	0	↕	IFF2	0	•	11 101 101	ED	2	2	9	
										01 011 111	5F				
LD I,A	I←A	•	•	•	•	•	•	•	•	11 101 101	ED	2	2	9	
										01 000 111	47				
LD R,A	R←A	•	•	•	•	•	•	•	•	11 101 101	ED	2	2	9	
										01 001 111	57				

8.2 16-Bit Load Group

Mnemonic	Symbolic Operation	SF	ZF	YF	HF	XF	PF	NF	CF	Opcode 76 543 210	Hex	Bytes	M Cycles	T States	Comments
LD dd,nn	dd←nn	•	•	•	•	•	•	•	•	00 dd0 001		3	3	10	dd Reg
										← n →					00 BC
										← n →					01 DE
LD IX,nn	IX←nn	•	•	•	•	•	•	•	•	11 011 101	DD	4	4	14	10 HL
										00 100 001	21				11 SP
										← n →					
										← n →					
LD IY,nn	IX←nn	•	•	•	•	•	•	•	•	11 111 101	FD	4	4	14	
										00 100 001	21				
										← n →					
										← n →					
LD HL,(nn)	H←(nn+1)	•	•	•	•	•	•	•	•	00 101 010	2A	3	5	16	
	L←(nn)									← n →					
										← n →					
LD dd,(nn)	ddh←(nn+1)	•	•	•	•	•	•	•	•	11 101 101	ED	4	6	20	
	ddl←(nn)									01 dd1 011					
										← n →					
										← n →					
LD IX,(nn)	IXh←(nn+1)	•	•	•	•	•	•	•	•	11 011 101	DD	4	6	20	
	IXl←(nn)									00 101 010	2A				
										← n →					
										← n →					
LD IY,(nn)	IYh←(nn+1)	•	•	•	•	•	•	•	•	11 111 101	FD	4	6	20	
	IYl←(nn)									00 101 010	2A				
										← n →					
										← n →					
LD (nn),HL	(nn+1)←H	•	•	•	•	•	•	•	•	00 100 010	22	3	5	16	
	(nn)←L									← n →					
										← n →					
LD (nn),dd	(nn+1)←ddh	•	•	•	•	•	•	•	•	11 101 101	ED	4	6	20	
	(nn)←ddl									01 dd0 011					
										← n →					
										← n →					
LD (nn),IX	(nn+1)←IXh	•	•	•	•	•	•	•	•	11 011 101	DD	4	6	20	
	(nn)←IXl									00 100 010	22				
										← n →					
										← n →					
LD (nn),IY	(nn+1)←IYh	•	•	•	•	•	•	•	•	11 111 101	FD	4	6	20	
	(nn)←IYl									00 100 010	22				
										← n →					
										← n →					
LD SP,HL	SP←HL	•	•	•	•	•	•	•	•	11 111 001	F9	1	1	6	
LD SP,IX	SP←IX	•	•	•	•	•	•	•	•	11 011 101	DD	2	2	10	
										11 111 001	F9				
LD SP,IY	SP←IY	•	•	•	•	•	•	•	•	11 111 101	FD	2	2	10	
										11 111 001	F9				

(continued)

Mnemonic	Symbolic Operation	SF	ZF	YF	HF	XF	PF	NF	CF	Opcode 76 543 210	Hex	Bytes	M Cycles	T States	Comments
PUSH qq	(SP-2)←qql	•	•	•	•	•	•	•	•	11 qq0 101		1	3	11	qq Reg
	(SP-1)←qqh														00 BC
	SP←SP-2														01 DE
PUSH IX	(SP-2)←IXl	•	•	•	•	•	•	•	•	11 011 101	DD	2	4	15	10 HL
	(SP-1)←IXh									11 100 101	E5				11 AF
	SP←SP-2														
PUSH IY	(SP-2)←IYl	•	•	•	•	•	•	•	•	11 111 101	FD	2	4	15	
	(SP-1)←IYh									11 100 101	E5				
	SP←SP-2														
POP qq	qqh←(SP+1)	•	•	•	•	•	•	•	•	11 qq0 001		1	3	10	
	qql←(SP)														
	SP←SP+2														
POP IX	IXh←(SP+1)	•	•	•	•	•	•	•	•	11 011 101	DD	2	4	14	
	IXl←(SP)									11 100 001	E1				
	SP←SP+2														
POP IY	IYh←(SP+1)	•	•	•	•	•	•	•	•	11 111 101	FD	2	4	14	
	IYl←(SP)									11 100 001	E1				
	SP←SP+2														

8.3 Exchange, Block Transfer, Block Search Group

Mnemonic	Symbolic Operation	SF	ZF	YF	HF	XF	PF	NF	CF	Opcode 76 543 210	Hex	Bytes	M Cycles	T States	Comments
EX DE,HL	DE↔HL	•	•	•	•	•	•	•	•	11 101 011	E8	1	1	4	
EX AF,AF'	AF↔AF'	•	•	•	•	•	•	•	•	00 001 000	08	1	1	4	
EXX	BC↔BC' DE↔DE' HL↔HL'	•	•	•	•	•	•	•	•	11 011 001	D8	1	1	4	
EX (SP),HL	H↔(SP+1) L↔(SP)	•	•	•	•	•	•	•	•	11 100 011	E3	1	5	19	
EX (SP),IX	IXh↔(SP+1) IXl↔(SP)	•	•	•	•	•	•	•	•	11 011 101 11 100 011	DD	2	6	23	
EX (SP),IY	IYh↔(SP+1) IYl↔(SP)	•	•	•	•	•	•	•	•	11 111 101 11 100 011	FD	2	6	23	
LDI	(DE)←(HL) DE←DE+1 HL←HL+1 BC←BC-1	•	•	↕[4]	0	↕[4]	↕[1]	0	•	11 101 101 10 100 000	ED A0	2	4	16	
LDIR	(DE)←(HL) DE←DE+1 HL←HL+1 BC←BC-1 Repeat until BC=0	•	•	↕[4]	0	↕[4]	0[2]	0	•	11 101 101 10 110 000	ED B0	2 2	5 4	21 16	if BC≠0 if BC=0
LDD	(DE)←(HL) DE←DE-1 HL←HL-1 BC←BC-1	•	•	↕[4]	0	↕[4]	↕[1]	0	•	11 101 101 10 101 000	ED A8	2	4	16	
LDDR	(DE)←(HL) DE←DE-1 HL←HL-1 BC←BC-1 Repeat until BC=0	•	•	↕[4]	0	↕[4]	0[2]	0	•	11 101 101 10 111 000	ED B8	2 2	5 4	21 16	if BC≠0 if BC=0
CPI	A-(HL) HL←HL+1 BC←BC-1	↕[4]	↕[3]	↕[4]	↕[4]	↕[4]	↕[1]	1	•	11 101 101 10 100 001	ED A1	2	4	16	
CPIR	A-(HL) HL←HL+1 BC←BC-1 Repeat until A=(HL) or BC=0	↕[4]	↕[3]	↕[4]	↕[4]	↕[4]	↕[1]	1	•	11 101 101 10 110 001	ED B1	2 2	5 4	21 18	if BC≠0 and A≠(HL) if BC=0 or A=(HL)
CPD	A-(HL) HL←HL-1 BC←BC-1	↕[4]	↕[3]	↕[4]	↕[4]	↕[4]	↕[1]	1	•	11 101 101 10 101 001	ED A9	2	4	16	
CPDR	A-(HL) HL←HL-1 BC←BC-1 Repeat until A=(HL) or BC=0	↕[4]	↕[3]	↕[4]	↕[4]	↕[4]	↕[1]	1	•	11 101 101 10 111 001	ED B9	2 2	5 4	21 18	if BC≠0 and A≠(HL) if BC=0 or A=(HL)

Note:
[1] PF is 0 the result of BC-1=0, otherwise PF is set.
[2] PF is 0 only at completion of the instruction.
[3] ZF is set if A=(HL), otherwise ZF is reset.
[4] See section 4.2 for a description.

8.4 8-Bit Arithmetic and Logical Group

Mnemonic	Symbolic Operation	SF	ZF	YF	HF	XF	PF	NF	CF	76	543	210	Hex	Bytes	M Cycles	T States	Comments
ADD A,r	A←A+r	↕	↕	↕	↕	↕	VF	0	↕	10	000	r		1	1	4	r Reg
ADD A,p	A←A+p	↕	↕	↕	↕	↕	VF	0	↕	11	011	101	DD	2	2	8	000 B
										10	000	p					001 C
ADD A,q	A←A+q	↕	↕	↕	↕	↕	VF	0	↕	11	111	101	FD	2	2	8	010 D
										10	000	q					011 E
ADD A,n	A←A+n	↕	↕	↕	↕	↕	VF	0	↕	11	000	110		2	2	7	100 H
										← n →							101 L
ADD A,(HL)	A←A+(HL)	↕	↕	↕	↕	↕	VF	0	↕	10	000	110		1	2	7	111 A
ADD A,(IX+d)	A←A+(IX+d)	↕	↕	↕	↕	↕	VF	0	↕	11	011	101	DD	3	5	19	
										10	000	110					
										← d →							p Reg
ADD A,(IY+d)	A←A+(IY+d)	↕	↕	↕	↕	↕	VF	0	↕	11	111	101	FD	3	5	19	000 B
										10	000	110					001 C
										← d →							010 D
ADC A,s	A←A+s+CF	↕	↕	↕	↕	↕	VF	0	↕		001						011 E
SUB s	A←A-s	↕	↕	↕	↕	↕	VF	1	↕		010						100 IXh
SBC s	A←A-s-CF	↕	↕	↕	↕	↕	VF	1	↕		011						101 IXl
AND s	A←A∧s	↕	↕	↕	1	↕	PF	0	0		100						111 A
OR s	A←A∨s	↕	↕	↕	0	↕	PF	0	0		110						
XOR s	A←A•s	↕	↕	↕	0	↕	PF	0	0		101						
CP s	A-s	↕	↕	↕[1]	↕	↕[1]	VF	1	↕		111						q Reg
INC r	r←r+1	↕	↕	↕	↕	↕	VF	0	•	00	r	100		1	1	4	000 B
INC p	p←p+1	↕	↕	↕	↕	↕	VF	0	•	11	011	101	DD	2	2	8	001 C
										00	p	100					010 D
INC q	q←q+1	↕	↕	↕	↕	↕	VF	0	•	11	111	101	FD	2	2	8	011 E
										00	q	100					100 IYh
INC (HL)	(HL)←(HL)+1	↕	↕	↕	↕	↕	VF	0	•	00	110	100		1	3	11	101 IYl
INC (IX+d)	(IX+d)←(IX+d)+1	↕	↕	↕	↕	↕	VF	0	•	11	011	101	DD	3	6	26	111 A
										00	110	100					
										← d →							
INC (IY+d)	(IY+d)←(IY+d)+1	↕	↕	↕	↕	↕	VF	0	•	11	111	101	FD	3	6	26	
										00	110	100					
										← d →							
DEC m	m←m-1	↕	↕	↕	↕	↕	VF	1	•		101						

Note: [1]YF and XF flags are copied from the operand s, not the result A-s
s is any of r, p, q, n, (HL), (IX+d), (IY+d) as shown for ADD. The indicated bits replace the 000 in the ADD set above
m is any of r, p, q, (HL), (IX+d), (IY+d) as shown for INC. Replace 100 with 101 in opcode

8.5 General-Purpose Arithmetic and CPU Control Group

Mnemonic	Symbolic Operation	SF	ZF	YF	HF	XF	PF	NF	CF	76	543	210	Hex	Bytes	M Cycles	T States	Comments
DAA		↕	↕	↕	↕	↕	PF	•	↕	00	100	111	27	1	1	4	Decimal adjust accumulator
CPL	A← $\overline{A}$	•	•	↕	1	↕	•	1	•	00	101	111	2F	1	1	4	Compliment
NEG	A←0-A	↕	↕	↕	↕	↕	VF	1	↕	11	011	101	ED	2	2	8	Negate
										01	000	100	44				
CCF	CF← $\overline{CF}$	•	•	↕[1]	↕[2]	↕[1]	•	0	↕	00	111	111	3F	1	1	4	
SCF	CF←1	•	•	↕[1]	0	↕[1]	•	0	1	00	110	111	37	1	1	4	
NOP		•	•	•	•	•	•	•	•	00	000	000	00	1	1	4	
HALT		•	•	•	•	•	•	•	•	01	110	110	76	1	1	4	
DI[3]	IFF1,2←0	•	•	•	•	•	•	•	•	11	110	011	F3	1	1	4	
EI[3]	IFF1,2←1	•	•	•	•	•	•	•	•	11	111	011	FB	1	1	4	
IM 0[4]		•	•	•	•	•	•	•	•	11	011	101	ED	2	2	8	
										01	000	110	46				
IM 1[4]		•	•	•	•	•	•	•	•	11	011	101	ED	2	2	8	
										01	010	110	56				
IM 2[4]		•	•	•	•	•	•	•	•	11	011	101	ED	2	2	8	
										01	011	110	5E				

Note: [1]YF and XF are copied from register A.
[2]HF is like CF before the instruction.
[3]No interrupts are accepted directly after EI or DI.
[4]This instruction has other undocumented opcodes.

8.6 16-Bit Arithmetic Group

Mnemonic	Symbolic Operation	SF	ZF	YF	HF	XF	PF	NF	CF	Opcode 76 543 210	Hex	Bytes	M Cycles	T States	Comments
ADD HL,ss	HL←HL+ss	•	•	↕[2]	↕[2]	↕[2]	•	0	↕[1]	01 ss1 001		1	3	11	ss Reg
ADC HL,ss	HL←HL+ss+CF	↕[1]	↕[1]	↕[2]	↕[2]	↕[2]	VF[1]	0	↕[1]	11 011 101	ED	2	4	15	00 BC
										01 ss1 010					01 DE
SBC HL,ss	HL←HL-ss-CF	↕[1]	↕[1]	↕[2]	↕[2]	↕[2]	VF[1]	0	↕[1]	11 011 101	ED	2	4	15	10 HL
										01 ss0 010					11 SP
ADD IX,pp	IX←IX+pp	•	•	↕[2]	↕[2]	↕[2]	•	0	↕[1]	11 011 110	DD	2	4	15	
										01 pp1 001					pp Reg
ADD IY,qq	IY←IY+qq	•	•	↕[2]	↕[2]	↕[2]	•	0	↕[1]	11 111 110	FD	2	4	15	00 BC
										01 pp1 001					01 DE
INC ss	ss←ss+1	•	•	•	•	•	•	•	•	00 ss0 011		1	1	6	10 IX
INC IX	IX←IX+1	•	•	•	•	•	•	•	•	11 011 101	DD	2	2	10	11 SP
										00 100 011	23				
INC IY	IY←IY+1	•	•	•	•	•	•	•	•	11 111 101	FD	2	2	10	qq Reg
										00 100 011	23				00 BC
DEC ss	ss←ss-1	•	•	•	•	•	•	•	•	00 ss1 011		1	1	6	01 DE
DEC IX	IX←IX-1	•	•	•	•	•	•	•	•	11 011 101	DD	2	2	10	10 HL
										00 101 011	2B				11 SP
DEC IY	IY←IY-1	•	•	•	•	•	•	•	•	11 111 101	FD	2	2	10	
										00 101 011	2B				

Note: [1]Flag is affected by the 16 bit result.
[2]Flag is affected by the high-byte addition.

8.7 Rotate and Shift Group

Mnemonic	Symbolic Operation	SF	ZF	YF	HF	XF	PF	NF	CF	Opcode 76 543 210	Hex	Bytes	M Cycles	T States	Comments
RLCA		•	•	↕	0	↕	•	0	↕	00 000 111	07	1	1	4	
RLA		•	•	↕	0	↕	•	0	↕	00 010 111	17	1	1	4	
RRCA		•	•	↕	0	↕	•	0	↕	00 001 111	0F	1	1	4	
RRA		•	•	↕	0	↕	•	0	↕	00 011 111	1F	1	1	4	
RLC r		↕	↕	↕	0	↕	PF	0	↕	11 001 011 00 [000] r	CB	2	2	8	r Reg 000 B
RLC (HL)		↕	↕	↕	0	↕	PF	0	↕	11 001 011 00 [000] 110	CB	2	4	15	001 C 010 D
RLC (IX+d)		↕	↕	↕	0	↕	PF	0	↕	11 011 101 11 001 011 ← d → 00 [000] 110	DD CB	4	6	23	011 E 100 H 101 L 111 A
RLC (IY+d)		↕	↕	↕	0	↕	PF	0	↕	11 111 101 11 001 011 ← d → 00 [000] 110	FD CB	4	6	23	
RLC (IX+d),r	r←(IX+d) RLC r (IX+d)←r	↕	↕	↕	0	↕	PF	0	↕	11 011 101 11 001 011 ← d → 00 [000] r	DD CB	4	6	23	
RLC (IY+d),r	r←(IY+d) RLC r (IY+d)←r	↕	↕	↕	0	↕	PF	0	↕	11 111 101 11 001 011 ← d → 00 [000] r	FD CB	4	6	23	
RL m		↕	↕	↕	0	↕	PF	0	↕	[010]					
RRC m		↕	↕	↕	0	↕	PF	0	↕	[001]					
RR m		↕	↕	↕	0	↕	PF	0	↕	[011]					
SLA m		↕	↕	↕	0	↕	PF	0	↕	[100]					
SLL m		↕	↕	↕	0	↕	PF	0	↕	[110]					
SRA m		↕	↕	↕	0	↕	PF	0	↕	[101]					
SLA m		↕	↕	↕	0	↕	PF	0	↕	[111]					
RLD		↕	↕	↕	0	↕	PF	0	•	11 101 101 01 101 111	ED 6F	2	5	18	
RRD		↕	↕	↕	0	↕	PF	0	•	11 101 101 01 100 111	ED 67	2	5	18	

Note: m is one of r,(HL),(IX+d),(IY+d). To form new opcode replace [000] of RLCs with shown code.

8.8 Bit Set, Reset and Test Group

Mnemonic	Symbolic Operation	SF	ZF	YF	HF	XF	PF	NF	CF	Opcode 76 543 210	Hex	Bytes	M Cycles	T States	Comments
BIT b,r	ZF← $\overline{r_b}$	↕[1]	↕	↕[1]	1	↕[1]	↕[1]	0	•	11 001 011 01 b r	CB	2	2	8	r Reg 000 B
BIT b,(HL)	ZF← $\overline{(HL)_b}$	↕[1]	↕	↕[1]	1	↕[1]	↕[1]	0	•	11 001 011 01 b 110	CB	2	3	12	001 C 010 D
BIT b,(IX+d)[2]	ZF← $\overline{(IX+d)_b}$	↕[1]	↕	↕[1]	1	↕[1]	↕[1]	0	•	11 011 101 11 001 011 ← d → 01 b 110	DD CB	4	8	20	011 E 100 H 101 L 111 A
BIT b,(IY+d)[2]	ZF← $\overline{(IY+d)_b}$	↕[1]	↕	↕[1]	1	↕[1]	↕[1]	0	•	11 111 101 11 001 011 ← d → 01 b 110	FD CB	4	8	20	
SET b,r	r_b ←1	•	•	•	•	•	•	•	•	11 001 011 11 b r	CB	2	2	8	b Bit 000 0
SET b,(HL)	$(HL)_b$ ←1	•	•	•	•	•	•	•	•	11 001 011 11 b 110	CB	2	4	15	001 1 010 2
SET b,(IX+d)	$(IX+d)_b$ ←1	•	•	•	•	•	•	•	•	11 011 101 11 001 011 ← d → 11 b 110	DD CB	4	8	23	011 3 100 4 101 5 110 6
SET b,(IY+d)	$(IY+d)_b$ ←1	•	•	•	•	•	•	•	•	11 111 101 11 001 011 ← d → 11 b 110	FD CB	4	8	23	111 7
SET b,(IX+d),r	r←(IX+d) r_b ←1 (IX+d)←r	•	•	•	•	•	•	•	•	11 011 101 11 001 011 ← d → 11 b r	DD CB	4	8	23	
SET b,(IY+d),r	r←(IY+d) r_b ←1 (IY+d)←r	•	•	•	•	•	•	•	•	11 111 101 11 001 011 ← d → 11 b r	FD CB	4	8	23	
RES b,m	m_b ←0	•	•	•	•	•	•	•	•	10					

Note: [1] See section 4.1 for a complete description.
[2] Instruction has other undocumented opcodes.
m is one of r, (HL), (IX+d), (IY+d). To form RES instruction, replace 11 with 10.

8.9 Jump Group

Mnemonic	Symbolic Operation	SF	ZF	YF	HF	XF	PF	NF	CF	Opcode 76 543 210	Hex	Bytes	M Cycles	T States	Comments
JP nn	PC←nn	•	•	•	•	•	•	•	•	11 000 011 ← n → ← n →	C3	3	3	10	cc Condition 000 NZ 001 Z
JP cc,nn	if cc PC←nn	•	•	•	•	•	•	•	•	11 cc 010 ← n → ← n →		3	3	10	010 NC 011 C 100 PO
JR e	PC←PC+e	•	•	•	•	•	•	•	•	00 011 000 ← e-2 →	18	2	3	12	101 PE 110 P 111 M
JR ss,e	if ss PC←PC+e	•	•	•	•	•	•	•	•	00 1ss 000 ← e-2 →		2 2	3 2	12 7	if ss is true if ss is false
JP (HL)	PC←HL	•	•	•	•	•	•	•	•	11 101 001	E9	1	1	4	
JP (IX)	PC←IX	•	•	•	•	•	•	•	•	11 011 101 11 101 001	DD E9	2	2	8	ss Condition 11 C
JP (IY)	PC←IY	•	•	•	•	•	•	•	•	11 111 101 11 101 001	FD E9	2	2	8	10 NC 01 Z 00 NZ
DJNZ e	B←B-1 if B≠0 PC←PC+e	•	•	•	•	•	•	•	•	00 010 000 ← e-2 →	10	2 2	2 3	10 13	if B=0 if B≠0

Note: e is a signed two-compliment in the range -127, 129.
e-2 in the opcode provides an effective number of PC+e as PC is incremented by two prior to the addition of e.

8.10 Call and Return Group

Mnemonic	Symbolic Operation	SF	ZF	YF	HF	XF	PF	NF	CF	Opcode 76 543 210	Hex	Bytes	M Cycles	T States	Comments
CALL nn	(SP-1)←PCh	•	•	•	•	•	•	•	•	11 001 101	CD	3	5	17	
	(SP-2)←PCl									← n →					
	SP←SP-2									← n →					
	PC←nn														
CALL cc,nn	if cc is true	•	•	•	•	•	•	•	•	11 cc 100		3	3	10	if cc is false
	(SP-1)←PCh									← n →		3	5	17	if cc is true
	(SP-2)←PCl									← n →					
	SP←SP-2														
	PC←nn														
RET	PCl←(SP)	•	•	•	•	•	•	•	•	11 001 001	C9	1	3	10	
	PCh←(SP+1)														
	SP←SP+2														
RET cc	if cc is true	•	•	•	•	•	•	•	•	11 cc 000		1	1	5	if cc is false
	PCl←(SP)											1	5	17	if cc is true
	PCh←(SP+1)														
	SP←SP+2														
RETI[1]	PCl←(SP)	•	•	•	•	•	•	•	•	11 101 101	ED	2	4	14	
	PCh←(SP+1)									01 001 101	4D				
	SP←SP+2														
RETN[2]	PCl←(SP)	•	•	•	•	•	•	•	•	11 101 101	ED	2	4	14	
	PCh←(SP+1)									01 000 101	45				
	SP←SP+2														
	IFF1←IFF2														
RST p	(SP-1)←PCh	•	•	•	•	•	•	•	•	11 t 111		1	3	11	
	(SP-2)←PCl									← n →					
	SP←SP-2									← n →					
	PC←p														

t	p
000	0h
001	8h
010	10h
011	18h
100	20h
101	28h
110	30h
111	38h

cc	Condition
000	NZ
001	Z
010	NC
011	C
100	PO
101	PE
110	P
111	M

Note:
[1] RETI also copies IFF2 into IFF1, like RETN.
[2] This instruction has other undocumented opcodes.

8.11 Input and Output Group

Mnemonic	Symbolic Operation	SF	ZF	YF	HF	XF	PF	NF	CF	Opcode 76 543 210	Hex	Bytes	M Cycles	T States	Comments
IN A,(n)	A←(n)	•	•	•	•	•	•	•	•	11 011 011 ← n →	DB	2	3	11	r Reg 000 B
IN r,(C)	r←(C)	↕	↕	↕	0	↕	PF	0	•	11 101 101 01 r 000	ED	2	3	12	001 C 010 D
IN F,(n)	←(C)	↕	↕	↕	0	↕	PF	0	•	11 101 101 01 110 000	ED 70	2	3	12	011 E 100 H
INI	(HL)←(C) HL←HL+1 B←B-1	↕[1]	↕[1]	↕[1]	↕[3]	↕[1]	X	↕[2]	↕[3]	11 101 101 10 100 010	ED A2	2	4	16	101 L 111 A
INIR	(HL)←(C) HL←HL+1 B←B-1 Repeat until B=0	0	1	0	↕[3]	0	X	↕[2]	↕[3]	11 101 101 10 110 010	ED B2	2 2	5 4	21 16	if B≠0 if B=0
IND	(HL)←(C) HL←HL-1 B←B-1	↕[1]	↕[1]	↕[1]	↕[4]	↕[1]	X	↕[2]	↕[4]	11 101 101 10 101 010	ED AA	2	4	16	
INDR	(HL)←(C) HL←HL-1 B←B-1 Repeat until B=0	0	1	0	↕[4]	0	X	↕[2]	↕[4]	11 101 101 10 111 010	ED BA	2 2	5 4	21 16	if B≠0 if B=0
OUT (n),A	(n)←A	•	•	•	•	•	•	•	•	11 010 011 ← n →	D3	2	3	11	
OUT (C),r	(C)←r	•	•	•	•	•	•	•	•	11 101 101 01 r 001	ED	2	3	12	
OUT (C),0	(C)←0	•	•	•	•	•	•	•	•	11 101 101 01 110 001	ED 71	2	3	12	
OUTI	(C)←(HL) HL←HL+1 B←B-1	↕[1]	↕[1]	↕[1]	↕[5]	↕[1]	X	↕[2]	↕[5]	11 101 101 10 100 011	ED A2	2	4	16	
OTIR	(C)←(HL) HL←HL+1 B←B-1 Repeat until B=0	0	1	0	↕[5]	0	X	↕[2]	↕[5]	11 101 101 10 110 011	ED B3	2 2	5 4	21 16	if B≠0 if B=0
OUTD	(C)←(HL) HL←HL-1 B←B-1	↕[1]	↕[1]	↕[1]	↕[5]	↕[1]	X	↕[2]	↕[5]	11 101 101 10 101 011	ED AA	2	4	16	
OTDR	(C)←(HL) HL←HL-1 B←B-1 Repeat until B=0	0	1	0	↕[5]	0	X	↕[2]	↕[5]	11 101 101 10 111 011	ED BB	2 2	5 4	21 16	if B≠0 if B=0

Note:
[1] flag is affected by the result of B←B-1 as in DEC B.
[2] NF is a copy of bit 7 of the transferred byte.
[3] This flag contains the carry of (((C+1) AND 255)+(C)), see section 4.3.
[4] This flag contains the carry of (((C-1) AND 255)+(C)), see section 4.3.
[5] This flag contains the carry of (L+(C)), see section 4.3.

Chapter 9

Instructions Sorted by Opcode

Any instruction marked with * is undocumented.

00	NOP	2D	DEC L	5A	LD E,D
01 n n	LD BC,nn	2E n	LD L,n	5B	LD E,E
02	LD (BC),A	2F	CPL	5C	LD E,H
03	INC BC	30 e	JR NC,(PC+e)	5D	LD E,L
04	INC B	31 n n	LD SP,nn	5E	LD E,(HL)
05	DEC B	32 n n	LD (nn),A	5F	LD E,A
06 n	LD B,n	33	INC SP	60	LD H,B
07	RLCA	34	INC (HL)	61	LD H,C
08	EX AF,AF'	35	DEC (HL)	62	LD H,D
09	ADD HL,BC	36 n	LD (HL),n	63	LD H,E
0A	LD A,(BC)	37	SCF	64	LD H,H
0B	DEC BC	38 e	JR C,(PC+e)	65	LD H,L
0C	INC C	39	ADD HL,SP	66	LD H,(HL)
0D	DEC C	3A n n	LD A,(nn)	67	LD H,A
0E n	LD C,n	3B	DEC SP	68	LD L,B
0F	RRCA	3C	INC A	69	LD L,C
10 e	DJNZ (PC+e)	3D	DEC A	6A	LD L,D
11 n n	LD DE,nn	3E n	LD A,n	6B	LD L,E
12	LD (DE),A	3F	CCF	6C	LD L,H
13	INC DE	40	LD B,B	6D	LD L,L
14	INC D	41	LD B,C	6E	LD L,(HL)
15	DEC D	42	LD B,D	6F	LD L,A
16 n	LD D,n	43	LD B,E	70	LD (HL),B
17	RLA	44	LD B,H	71	LD (HL),C
18 e	JR (PC+e)	45	LD B,L	72	LD (HL),D
19	ADD HL,DE	46	LD B,(HL)	73	LD (HL),E
1A	LD A,(DE)	47	LD B,A	74	LD (HL),H
1B	DEC DE	48	LD C,B	75	LD (HL),L
1C	INC E	49	LD C,C	76	HALT
1D	DEC E	4A	LD C,D	77	LD (HL),A
1E n	LD E,n	4B	LD C,E	78	LD A,B
1F	RRA	4C	LD C,H	79	LD A,C
20 e	JR NZ,(PC+e)	4D	LD C,L	7A	LD A,D
21 n n	LD HL,nn	4E	LD C,(HL)	7B	LD A,E
22 n n	LD (nn),HL	4F	LD C,A	7C	LD A,H
23	INC HL	50	LD D,B	7D	LD A,L
24	INC H	51	LD D,C	7E	LD A,(HL)
25	DEC H	52	LD D,D	7F	LD A,A
26 n	LD H,n	53	LD D,E	80	ADD A,B
27	DAA	54	LD D,H	81	ADD A,C
28 e	JR Z,(PC+e)	55	LD D,L	82	ADD A,D
29	ADD HL,HL	56	LD D,(HL)	83	ADD A,E
2A n n	LD HL,(nn)	57	LD D,A	84	ADD A,H
2B	DEC HL	58	LD E,B	85	ADD A,L
2C	INC L	59	LD E,C	86	ADD A,(HL)

87	ADD A,A	CB06	RLC (HL)	CB50	BIT 2,B
88	ADC A,B	CB07	RLC A	CB51	BIT 2,C
89	ADC A,C	CB08	RRC B	CB52	BIT 2,D
8A	ADC A,D	CB09	RRC C	CB53	BIT 2,E
8B	ADC A,E	CB0A	RRC D	CB54	BIT 2,H
8C	ADC A,H	CB0B	RRC E	CB55	BIT 2,L
8D	ADC A,L	CB0C	RRC H	CB56	BIT 2,(HL)
8E	ADC A,(HL)	CB0D	RRC L	CB57	BIT 2,A
8F	ADC A,A	CB0E	RRC (HL)	CB58	BIT 3,B
90	SUB B	CB0F	RRC A	CB59	BIT 3,C
91	SUB C	CB10	RL B	CB5A	BIT 3,D
92	SUB D	CB11	RL C	CB5B	BIT 3,E
93	SUB E	CB12	RL D	CB5C	BIT 3,H
94	SUB H	CB13	RL E	CB5D	BIT 3,L
95	SUB L	CB14	RL H	CB5E	BIT 3,(HL)
96	SUB (HL)	CB15	RL L	CB5F	BIT 3,A
97	SUB A	CB16	RL (HL)	CB60	BIT 4,B
98	SBC A,B	CB17	RL A	CB61	BIT 4,C
99	SBC A,C	CB18	RR B	CB62	BIT 4,D
9A	SBC A,D	CB19	RR C	CB63	BIT 4,E
9B	SBC A,E	CB1A	RR D	CB64	BIT 4,H
9C	SBC A,H	CB1B	RR E	CB65	BIT 4,L
9D	SBC A,L	CB1C	RR H	CB66	BIT 4,(HL)
9E	SBC A,(HL)	CB1D	RR L	CB67	BIT 4,A
9F	SBC A,A	CB1E	RR (HL)	CB68	BIT 5,B
A0	AND B	CB1F	RR A	CB69	BIT 5,C
A1	AND C	CB20	SLA B	CB6A	BIT 5,D
A2	AND D	CB21	SLA C	CB6B	BIT 5,E
A3	AND E	CB22	SLA D	CB6C	BIT 5,H
A4	AND H	CB23	SLA E	CB6D	BIT 5,L
A5	AND L	CB24	SLA H	CB6E	BIT 5,(HL)
A6	AND (HL)	CB25	SLA L	CB6F	BIT 5,A
A7	AND A	CB26	SLA (HL)	CB70	BIT 6,B
A8	XOR B	CB27	SLA A	CB71	BIT 6,C
A9	XOR C	CB28	SRA B	CB72	BIT 6,D
AA	XOR D	CB29	SRA C	CB73	BIT 6,E
AB	XOR E	CB2A	SRA D	CB74	BIT 6,H
AC	XOR H	CB2B	SRA E	CB75	BIT 6,L
AD	XOR L	CB2C	SRA H	CB76	BIT 6,(HL)
AE	XOR (HL)	CB2D	SRA L	CB77	BIT 6,A
AF	XOR A	CB2E	SRA (HL)	CB78	BIT 7,B
B0	OR B	CB2F	SRA A	CB79	BIT 7,C
B1	OR C	CB30	SLL B*	CB7A	BIT 7,D
B2	OR D	CB31	SLL C*	CB7B	BIT 7,E
B3	OR E	CB32	SLL D*	CB7C	BIT 7,H
B4	OR H	CB33	SLL E*	CB7D	BIT 7,L
B5	OR L	CB34	SLL H*	CB7E	BIT 7,(HL)
B6	OR (HL)	CB35	SLL L*	CB7F	BIT 7,A
B7	OR A	CB36	SLL (HL)*	CB80	RES 0,B
B8	CP B	CB37	SLL A*	CB81	RES 0,C
B9	CP C	CB38	SRL B	CB82	RES 0,D
BA	CP D	CB39	SRL C	CB83	RES 0,E
BB	CP E	CB3A	SRL D	CB84	RES 0,H
BC	CP H	CB3B	SRL E	CB85	RES 0,L
BD	CP L	CB3C	SRL H	CB86	RES 0,(HL)
BE	CP (HL)	CB3D	SRL L	CB87	RES 0,A
BF	CP A	CB3E	SRL (HL)	CB88	RES 1,B
C0	RET NZ	CB3F	SRL A	CB89	RES 1,C
C1	POP BC	CB40	BIT 0,B	CB8A	RES 1,D
C2 n n	JP NZ,(nn)	CB41	BIT 0,C	CB8B	RES 1,E
C3 n n	JP (nn)	CB42	BIT 0,D	CB8C	RES 1,H
C4 n n	CALL NZ,(nn)	CB43	BIT 0,E	CB8D	RES 1,L
C5	PUSH BC	CB44	BIT 0,H	CB8E	RES 1,(HL)
C6 n	ADD A,n	CB45	BIT 0,L	CB8F	RES 1,A
C7	RST 0H	CB46	BIT 0,(HL)	CB90	RES 2,B
C8	RET Z	CB47	BIT 0,A	CB91	RES 2,C
C9	RET	CB48	BIT 1,B	CB92	RES 2,D
CA n n	JP Z,(nn)	CB49	BIT 1,C	CB93	RES 2,E
CB00	RLC B	CB4A	BIT 1,D	CB94	RES 2,H
CB01	RLC C	CB4B	BIT 1,E	CB95	RES 2,L
CB02	RLC D	CB4C	BIT 1,H	CB96	RES 2,(HL)
CB03	RLC E	CB4D	BIT 1,L	CB97	RES 2,A
CB04	RLC H	CB4E	BIT 1,(HL)	CB98	RES 3,B
CB05	RLC L	CB4F	BIT 1,A	CB99	RES 3,C

CB9A	RES 3,D	CBE4	SET 4,H	DD5E d	LD E,(IX+d)
CB9B	RES 3,E	CBE5	SET 4,L	DD60	LD IXh,B*
CB9C	RES 3,H	CBE6	SET 4,(HL)	DD61	LD IXh,C*
CB9D	RES 3,L	CBE7	SET 4,A	DD62	LD IXh,D*
CB9E	RES 3,(HL)	CBE8	SET 5,B	DD63	LD IXh,E*
CB9F	RES 3,A	CBE9	SET 5,C	DD64	LD IXh,IXh*
CBA0	RES 4,B	CBEA	SET 5,D	DD65	LD IXh,IXl*
CBA1	RES 4,C	CBEB	SET 5,E	DD66 d	LD H,(IX+d)
CBA2	RES 4,D	CBEC	SET 5,H	DD67	LD IXh,A*
CBA3	RES 4,E	CBED	SET 5,L	DD68	LD IXl,B*
CBA4	RES 4,H	CBEE	SET 5,(HL)	DD69	LD IXl,C*
CBA5	RES 4,L	CBEF	SET 5,A	DD6A	LD IXl,D*
CBA6	RES 4,(HL)	CBF0	SET 6,B	DD6B	LD IXl,E*
CBA7	RES 4,A	CBF1	SET 6,C	DD6C	LD IXl,IXh*
CBA8	RES 5,B	CBF2	SET 6,D	DD6D	LD IXl,IXl*
CBA9	RES 5,C	CBF3	SET 6,E	DD6E d	LD L,(IX+d)
CBAA	RES 5,D	CBF4	SET 6,H	DD6F	LD IXl,A*
CBAB	RES 5,E	CBF5	SET 6,L	DD70 d	LD (IX+d),B
CBAC	RES 5,H	CBF6	SET 6,(HL)	DD71 d	LD (IX+d),C
CBAD	RES 5,L	CBF7	SET 6,A	DD72 d	LD (IX+d),D
CBAE	RES 5,(HL)	CBF8	SET 7,B	DD73 d	LD (IX+d),E
CBAF	RES 5,A	CBF9	SET 7,C	DD74 d	LD (IX+d),H
CBB0	RES 6,B	CBFA	SET 7,D	DD75 d	LD (IX+d),L
CBB1	RES 6,C	CBFB	SET 7,E	DD77 d	LD (IX+d),A
CBB2	RES 6,D	CBFC	SET 7,H	DD7C	LD A,IXh*
CBB3	RES 6,E	CBFD	SET 7,L	DD7D	LD A,IXl*
CBB4	RES 6,H	CBFE	SET 7,(HL)	DD7E d	LD A,(IX+d)
CBB5	RES 6,L	CBFF	SET 7,A	DD84	ADD A,IXh*
CBB6	RES 6,(HL)	CC n n	CALL Z,(nn)	DD85	ADD A,IXl*
CBB7	RES 6,A	CD n n	CALL (nn)	DD86 d	ADD A,(IX+d)
CBB8	RES 7,B	CE n	ADC A,n	DD8C	ADC A,IXh*
CBB9	RES 7,C	CF	RST 8H	DD8D	ADC A,IXl*
CBBA	RES 7,D	D0	RET NC	DD8E d	ADC A,(IX+d)
CBBB	RES 7,E	D1	POP DE	DD94	SUB IXh*
CBBC	RES 7,H	D2 n n	JP NC,(nn)	DD95	SUB IXl*
CBBD	RES 7,L	D3 n	OUT (n),A	DD96 d	SUB (IX+d)
CBBE	RES 7,(HL)	D4 n n	CALL NC,(nn)	DD9C	SBC A,IXh*
CBBF	RES 7,A	D5	PUSH DE	DD9D	SBC A,IXl*
CBC0	SET 0,B	D6 n	SUB n	DD9E d	SBC A,(IX+d)
CBC1	SET 0,C	D7	RST 10H	DDA4	AND IXh*
CBC2	SET 0,D	D8	RET C	DDA5	AND IXl*
CBC3	SET 0,E	D9	EXX	DDA6 d	AND (IX+d)
CBC4	SET 0,H	DA n n	JP C,(nn)	DDAC	XOR IXh*
CBC5	SET 0,L	DB n	IN A,(n)	DDAD	XOR IXl*
CBC6	SET 0,(HL)	DC n n	CALL C,(nn)	DDAE d	XOR (IX+d)
CBC7	SET 0,A	DD09	ADD IX,BC	DDB4	OR IXh*
CBC8	SET 1,B	DD19	ADD IX,DE	DDB5	OR IXl*
CBC9	SET 1,C	DD21 n n	LD IX,nn	DDB6 d	OR (IX+d)
CBCA	SET 1,D	DD22 n n	LD (nn),IX	DDBC	CP IXh*
CBCB	SET 1,E	DD23	INC IX	DDBD	CP IXl*
CBCC	SET 1,H	DD24	INC IXh*	DDBE d	CP (IX+d)
CBCD	SET 1,L	DD25	DEC IXh*	DDCB d 00	RLC (IX+d),B*
CBCE	SET 1,(HL)	DD26 n	LD IXh,n*	DDCB d 01	RLC (IX+d),C*
CBCF	SET 1,A	DD29	ADD IX,IX	DDCB d 02	RLC (IX+d),D*
CBD0	SET 2,B	DD2A n n	LD IX,(nn)	DDCB d 03	RLC (IX+d),E*
CBD1	SET 2,C	DD2B	DEC IX	DDCB d 04	RLC (IX+d),H*
CBD2	SET 2,D	DD2C	INC IXl*	DDCB d 05	RLC (IX+d),L*
CBD3	SET 2,E	DD2D	DEC IXl*	DDCB d 06	RLC (IX+d)
CBD4	SET 2,H	DD2E n	LD IXl,n*	DDCB d 07	RLC (IX+d),A*
CBD5	SET 2,L	DD34 d	INC (IX+d)	DDCB d 08	RRC (IX+d),B*
CBD6	SET 2,(HL)	DD35 d	DEC (IX+d)	DDCB d 09	RRC (IX+d),C*
CBD7	SET 2,A	DD36 d n	LD (IX+d),n	DDCB d 0A	RRC (IX+d),D*
CBD8	SET 3,B	DD39	ADD IX,SP	DDCB d 0B	RRC (IX+d),E*
CBD9	SET 3,C	DD44	LD B,IXh*	DDCB d 0C	RRC (IX+d),H*
CBDA	SET 3,D	DD45	LD B,IXl*	DDCB d 0D	RRC (IX+d),L*
CBDB	SET 3,E	DD46 d	LD B,(IX+d)	DDCB d 0E	RRC (IX+d)
CBDC	SET 3,H	DD4C	LD C,IXh*	DDCB d 0F	RRC (IX+d),A*
CBDD	SET 3,L	DD4D	LD C,IXl*	DDCB d 10	RL (IX+d),B*
CBDE	SET 3,(HL)	DD4E d	LD C,(IX+d)	DDCB d 11	RL (IX+d),C*
CBDF	SET 3,A	DD54	LD D,IXh*	DDCB d 12	RL (IX+d),D*
CBE0	SET 4,B	DD55	LD D,IXl*	DDCB d 13	RL (IX+d),E*
CBE1	SET 4,C	DD56 d	LD D,(IX+d)	DDCB d 14	RL (IX+d),H*
CBE2	SET 4,D	DD5C	LD E,IXh*	DDCB d 15	RL (IX+d),L*
CBE3	SET 4,E	DD5D	LD E,IXl*	DDCB d 16	RL (IX+d)

DDCB d 17	RL (IX+d),A*	DDCB d 61	BIT 4,(IX+d)*	DDCB d AB	RES 5,(IX+d),E*
DDCB d 18	RR (IX+d),B*	DDCB d 62	BIT 4,(IX+d)*	DDCB d AC	RES 5,(IX+d),H*
DDCB d 19	RR (IX+d),C*	DDCB d 63	BIT 4,(IX+d)*	DDCB d AD	RES 5,(IX+d),L*
DDCB d 1A	RR (IX+d),D*	DDCB d 64	BIT 4,(IX+d)*	DDCB d AE	RES 5,(IX+d)
DDCB d 1B	RR (IX+d),E*	DDCB d 65	BIT 4,(IX+d)*	DDCB d AF	RES 5,(IX+d),A*
DDCB d 1C	RR (IX+d),H*	DDCB d 66	BIT 4,(IX+d)	DDCB d B0	RES 6,(IX+d),B*
DDCB d 1D	RR (IX+d),L*	DDCB d 67	BIT 4,(IX+d)*	DDCB d B1	RES 6,(IX+d),C*
DDCB d 1E	RR (IX+d)	DDCB d 68	BIT 5,(IX+d)*	DDCB d B2	RES 6,(IX+d),D*
DDCB d 1F	RR (IX+d),A*	DDCB d 69	BIT 5,(IX+d)*	DDCB d B3	RES 6,(IX+d),E*
DDCB d 20	SLA (IX+d),B*	DDCB d 6A	BIT 5,(IX+d)*	DDCB d B4	RES 6,(IX+d),H*
DDCB d 21	SLA (IX+d),C*	DDCB d 6B	BIT 5,(IX+d)*	DDCB d B5	RES 6,(IX+d),L*
DDCB d 22	SLA (IX+d),D*	DDCB d 6C	BIT 5,(IX+d)*	DDCB d B6	RES 6,(IX+d)
DDCB d 23	SLA (IX+d),E*	DDCB d 6D	BIT 5,(IX+d)*	DDCB d B7	RES 6,(IX+d),A*
DDCB d 24	SLA (IX+d),H*	DDCB d 6E	BIT 5,(IX+d)	DDCB d B8	RES 7,(IX+d),B*
DDCB d 25	SLA (IX+d),L*	DDCB d 6F	BIT 5,(IX+d)*	DDCB d B9	RES 7,(IX+d),C*
DDCB d 26	SLA (IX+d)	DDCB d 70	BIT 6,(IX+d)*	DDCB d BA	RES 7,(IX+d),D*
DDCB d 27	SLA (IX+d),A*	DDCB d 71	BIT 6,(IX+d)*	DDCB d BB	RES 7,(IX+d),E*
DDCB d 28	SRA (IX+d),B*	DDCB d 72	BIT 6,(IX+d)*	DDCB d BC	RES 7,(IX+d),H*
DDCB d 29	SRA (IX+d),C*	DDCB d 73	BIT 6,(IX+d)*	DDCB d BD	RES 7,(IX+d),L*
DDCB d 2A	SRA (IX+d),D*	DDCB d 74	BIT 6,(IX+d)*	DDCB d BE	RES 7,(IX+d)
DDCB d 2B	SRA (IX+d),E*	DDCB d 75	BIT 6,(IX+d)*	DDCB d BF	RES 7,(IX+d),A*
DDCB d 2C	SRA (IX+d),H*	DDCB d 76	BIT 6,(IX+d)	DDCB d C0	SET 0,(IX+d),B*
DDCB d 2D	SRA (IX+d),L*	DDCB d 77	BIT 6,(IX+d)*	DDCB d C1	SET 0,(IX+d),C*
DDCB d 2E	SRA (IX+d)	DDCB d 78	BIT 7,(IX+d)*	DDCB d C2	SET 0,(IX+d),D*
DDCB d 2F	SRA (IX+d),A*	DDCB d 79	BIT 7,(IX+d)*	DDCB d C3	SET 0,(IX+d),E*
DDCB d 30	SLL (IX+d),B*	DDCB d 7A	BIT 7,(IX+d)*	DDCB d C4	SET 0,(IX+d),H*
DDCB d 31	SLL (IX+d),C*	DDCB d 7B	BIT 7,(IX+d)*	DDCB d C5	SET 0,(IX+d),L*
DDCB d 32	SLL (IX+d),D*	DDCB d 7C	BIT 7,(IX+d)*	DDCB d C6	SET 0,(IX+d)
DDCB d 33	SLL (IX+d),E*	DDCB d 7D	BIT 7,(IX+d)*	DDCB d C7	SET 0,(IX+d),A*
DDCB d 34	SLL (IX+d),H*	DDCB d 7E	BIT 7,(IX+d)	DDCB d C8	SET 1,(IX+d),B*
DDCB d 35	SLL (IX+d),L*	DDCB d 7F	BIT 7,(IX+d)*	DDCB d C9	SET 1,(IX+d),C*
DDCB d 36	SLL (IX+d)*	DDCB d 80	RES 0,(IX+d),B*	DDCB d CA	SET 1,(IX+d),D*
DDCB d 37	SLL (IX+d),A*	DDCB d 81	RES 0,(IX+d),C*	DDCB d CB	SET 1,(IX+d),E*
DDCB d 38	SRL (IX+d),B*	DDCB d 82	RES 0,(IX+d),D*	DDCB d CC	SET 1,(IX+d),H*
DDCB d 39	SRL (IX+d),C*	DDCB d 83	RES 0,(IX+d),E*	DDCB d CD	SET 1,(IX+d),L*
DDCB d 3A	SRL (IX+d),D*	DDCB d 84	RES 0,(IX+d),H*	DDCB d CE	SET 1,(IX+d)
DDCB d 3B	SRL (IX+d),E*	DDCB d 85	RES 0,(IX+d),L*	DDCB d CF	SET 1,(IX+d),A*
DDCB d 3C	SRL (IX+d),H*	DDCB d 86	RES 0,(IX+d)	DDCB d D0	SET 2,(IX+d),B*
DDCB d 3D	SRL (IX+d),L*	DDCB d 87	RES 0,(IX+d),A*	DDCB d D1	SET 2,(IX+d),C*
DDCB d 3E	SRL (IX+d)	DDCB d 88	RES 1,(IX+d),B*	DDCB d D2	SET 2,(IX+d),D*
DDCB d 3F	SRL (IX+d),A*	DDCB d 89	RES 1,(IX+d),C*	DDCB d D3	SET 2,(IX+d),E*
DDCB d 40	BIT 0,(IX+d)*	DDCB d 8A	RES 1,(IX+d),D*	DDCB d D4	SET 2,(IX+d),H*
DDCB d 41	BIT 0,(IX+d)*	DDCB d 8B	RES 1,(IX+d),E*	DDCB d D5	SET 2,(IX+d),L*
DDCB d 42	BIT 0,(IX+d)*	DDCB d 8C	RES 1,(IX+d),H*	DDCB d D6	SET 2,(IX+d)
DDCB d 43	BIT 0,(IX+d)*	DDCB d 8D	RES 1,(IX+d),L*	DDCB d D7	SET 2,(IX+d),A*
DDCB d 44	BIT 0,(IX+d)*	DDCB d 8E	RES 1,(IX+d)	DDCB d D8	SET 3,(IX+d),B*
DDCB d 45	BIT 0,(IX+d)*	DDCB d 8F	RES 1,(IX+d),A*	DDCB d D9	SET 3,(IX+d),C*
DDCB d 46	BIT 0,(IX+d)	DDCB d 90	RES 2,(IX+d),B*	DDCB d DA	SET 3,(IX+d),D*
DDCB d 47	BIT 0,(IX+d)*	DDCB d 91	RES 2,(IX+d),C*	DDCB d DB	SET 3,(IX+d),E*
DDCB d 48	BIT 1,(IX+d)*	DDCB d 92	RES 2,(IX+d),D*	DDCB d DC	SET 3,(IX+d),H*
DDCB d 49	BIT 1,(IX+d)*	DDCB d 93	RES 2,(IX+d),E*	DDCB d DD	SET 3,(IX+d),L*
DDCB d 4A	BIT 1,(IX+d)*	DDCB d 94	RES 2,(IX+d),H*	DDCB d DE	SET 3,(IX+d)
DDCB d 4B	BIT 1,(IX+d)*	DDCB d 95	RES 2,(IX+d),L*	DDCB d DF	SET 3,(IX+d),A*
DDCB d 4C	BIT 1,(IX+d)*	DDCB d 96	RES 2,(IX+d)	DDCB d E0	SET 4,(IX+d),B*
DDCB d 4D	BIT 1,(IX+d)*	DDCB d 97	RES 2,(IX+d),A*	DDCB d E1	SET 4,(IX+d),C*
DDCB d 4E	BIT 1,(IX+d)	DDCB d 98	RES 3,(IX+d),B*	DDCB d E2	SET 4,(IX+d),D*
DDCB d 4F	BIT 1,(IX+d)*	DDCB d 99	RES 3,(IX+d),C*	DDCB d E3	SET 4,(IX+d),E*
DDCB d 50	BIT 2,(IX+d)*	DDCB d 9A	RES 3,(IX+d),D*	DDCB d E4	SET 4,(IX+d),H*
DDCB d 51	BIT 2,(IX+d)*	DDCB d 9B	RES 3,(IX+d),E*	DDCB d E5	SET 4,(IX+d),L*
DDCB d 52	BIT 2,(IX+d)*	DDCB d 9C	RES 3,(IX+d),H*	DDCB d E6	SET 4,(IX+d)
DDCB d 53	BIT 2,(IX+d)*	DDCB d 9D	RES 3,(IX+d),L*	DDCB d E7	SET 4,(IX+d),A*
DDCB d 54	BIT 2,(IX+d)*	DDCB d 9E	RES 3,(IX+d)	DDCB d E8	SET 5,(IX+d),B*
DDCB d 55	BIT 2,(IX+d)*	DDCB d 9F	RES 3,(IX+d),A*	DDCB d E9	SET 5,(IX+d),C*
DDCB d 56	BIT 2,(IX+d)	DDCB d A0	RES 4,(IX+d),B*	DDCB d EA	SET 5,(IX+d),D*
DDCB d 57	BIT 2,(IX+d)*	DDCB d A1	RES 4,(IX+d),C*	DDCB d EB	SET 5,(IX+d),E*
DDCB d 58	BIT 3,(IX+d)*	DDCB d A2	RES 4,(IX+d),D*	DDCB d EC	SET 5,(IX+d),H*
DDCB d 59	BIT 3,(IX+d)*	DDCB d A3	RES 4,(IX+d),E*	DDCB d ED	SET 5,(IX+d),L*
DDCB d 5A	BIT 3,(IX+d)*	DDCB d A4	RES 4,(IX+d),H*	DDCB d EE	SET 5,(IX+d)
DDCB d 5B	BIT 3,(IX+d)*	DDCB d A5	RES 4,(IX+d),L*	DDCB d EF	SET 5,(IX+d),A*
DDCB d 5C	BIT 3,(IX+d)*	DDCB d A6	RES 4,(IX+d)	DDCB d F0	SET 6,(IX+d),B*
DDCB d 5D	BIT 3,(IX+d)*	DDCB d A7	RES 4,(IX+d),A*	DDCB d F1	SET 6,(IX+d),C*
DDCB d 5E	BIT 3,(IX+d)	DDCB d A8	RES 5,(IX+d),B*	DDCB d F2	SET 6,(IX+d),D*
DDCB d 5F	BIT 3,(IX+d)*	DDCB d A9	RES 5,(IX+d),C*	DDCB d F3	SET 6,(IX+d),E*
DDCB d 60	BIT 4,(IX+d)*	DDCB d AA	RES 5,(IX+d),D*	DDCB d F4	SET 6,(IX+d),H*

DDCB d F5	SET 6,(IX+d),L*	ED6B n n	LD HL,(nn)	FD54	LD D,IYh*
DDCB d F6	SET 6,(IX+d)	ED6C	NEG*	FD55	LD D,IYl*
DDCB d F7	SET 6,(IX+d),A*	ED6D	RETN*	FD56 d	LD D,(IY+d)
DDCB d F8	SET 7,(IX+d),B*	ED6E	IM 0*	FD5C	LD E,IYh*
DDCB d F9	SET 7,(IX+d),C*	ED6F	RLD	FD5D	LD E,IYl*
DDCB d FA	SET 7,(IX+d),D*	ED70	IN F,(C)* / IN (C)*	FD5E d	LD E,(IY+d)
DDCB d FB	SET 7,(IX+d),E*	ED71	OUT (C),0*	FD60	LD IYh,B*
DDCB d FC	SET 7,(IX+d),H*	ED72	SBC HL,SP	FD61	LD IYh,C*
DDCB d FD	SET 7,(IX+d),L*	ED73 n n	LD (nn),SP	FD62	LD IYh,D*
DDCB d FE	SET 7,(IX+d)	ED74	NEG*	FD63	LD IYh,E*
DDCB d FF	SET 7,(IX+d),A*	ED75	RETN*	FD64	LD IYh,IYh*
DDE1	POP IX	ED76	IM 1*	FD65	LD IYh,IYl*
DDE3	EX (SP),IX	ED78	IN A,(C)	FD66 d	LD H,(IY+d)
DDE5	PUSH IX	ED79	OUT (C),A	FD67	LD IYh,A*
DDE9	JP (IX)	ED7A	ADC HL,SP	FD68	LD IYl,B*
DDF9	LD SP,IX	ED7B n n	LD SP,(nn)	FD69	LD IYl,C*
DE n	SBC A,n	ED7C	NEG*	FD6A	LD IYl,D*
DF	RST 18H	ED7D	RETN*	FD6B	LD IYl,E*
E0	RET PO	ED7E	IM 2*	FD6C	LD IYl,IYh*
E1	POP HL	EDA0	LDI	FD6D	LD IYl,IYl*
E2 n n	JP PO,(nn)	EDA1	CPI	FD6E d	LD L,(IY+d)
E3	EX (SP),HL	EDA2	INI	FD6F	LD IYl,A*
E4 n n	CALL PO,(nn)	EDA3	OUTI	FD70 d	LD (IY+d),B
E5	PUSH HL	EDA8	LDD	FD71 d	LD (IY+d),C
E6 n	AND n	EDA9	CPD	FD72 d	LD (IY+d),D
E7	RST 20H	EDAA	IND	FD73 d	LD (IY+d),E
E8	RET PE	EDAB	OUTD	FD74 d	LD (IY+d),H
E9	JP (HL)	EDB0	LDIR	FD75 d	LD (IY+d),L
EA n n	JP PE,(nn)	EDB1	CPIR	FD77 d	LD (IY+d),A
EB	EX DE,HL	EDB2	INIR	FD7C	LD A,IYh*
EC n n	CALL PE,(nn)	EDB3	OTIR	FD7D	LD A,IYl*
ED40	IN B,(C)	EDB8	LDDR	FD7E d	LD A,(IY+d)
ED41	OUT (C),B	EDB9	CPDR	FD84	ADD A,IYh*
ED42	SBC HL,BC	EDBA	INDR	FD85	ADD A,IYl*
ED43 n n	LD (nn),BC	EDBB	OTDR	FD86 d	ADD A,(IY+d)
ED44	NEG	EE n	XOR n	FD8C	ADC A,IYh*
ED45	RETN	EF	RST 28H	FD8D	ADC A,IYl*
ED46	IM 0	F0	RET P	FD8E d	ADC A,(IY+d)
ED47	LD I,A	F1	POP AF	FD94	SUB IYh*
ED48	IN C,(C)	F2 n n	JP P,(nn)	FD95	SUB IYl*
ED49	OUT (C),C	F3	DI	FD96 d	SUB (IY+d)
ED4A	ADC HL,BC	F4 n n	CALL P,(nn)	FD9C	SBC A,IYh*
ED4B n n	LD BC,(nn)	F5	PUSH AF	FD9D	SBC A,IYl*
ED4C	NEG*	F6 n	OR n	FD9E d	SBC A,(IY+d)
ED4D	RETI	F7	RST 30H	FDA4	AND IYh*
ED4E	IM 0*	F8	RET M	FDA5	AND IYl*
ED4F	LD R,A	F9	LD SP,HL	FDA6 d	AND (IY+d)
ED50	IN D,(C)	FA n n	JP M,(nn)	FDAC	XOR IYh*
ED51	OUT (C),D	FB	EI	FDAD	XOR IYl*
ED52	SBC HL,DE	FC n n	CALL M,(nn)	FDAE d	XOR (IY+d)
ED53 n n	LD (nn),DE	FD09	ADD IY,BC	FDB4	OR IYh*
ED54	NEG*	FD19	ADD IY,DE	FDB5	OR IYl*
ED55	RETN*	FD21 n n	LD IY,nn	FDB6 d	OR (IY+d)
ED56	IM 1	FD22 n n	LD (nn),IY	FDBC	CP IYh*
ED57	LD A,I	FD23	INC IY	FDBD	CP IYl*
ED58	IN E,(C)	FD24	INC IYh*	FDBE d	CP (IY+d)
ED59	OUT (C),E	FD25	DEC IYh*	FDCB d 00	RLC (IY+d),B*
ED5A	ADC HL,DE	FD26 n	LD IYh,n*	FDCB d 01	RLC (IY+d),C*
ED5B n n	LD DE,(nn)	FD29	ADD IY,IY	FDCB d 02	RLC (IY+d),D*
ED5C	NEG*	FD2A n n	LD IY,(nn)	FDCB d 03	RLC (IY+d),E*
ED5D	RETN*	FD2B	DEC IY	FDCB d 04	RLC (IY+d),H*
ED5E	IM 2	FD2C	INC IYl*	FDCB d 05	RLC (IY+d),L*
ED5F	LD A,R	FD2D	DEC IYl*	FDCB d 06	RLC (IY+d)
ED60	IN H,(C)	FD2E n	LD IYl,n*	FDCB d 07	RLC (IY+d),A*
ED61	OUT (C),H	FD34 d	INC (IY+d)	FDCB d 08	RRC (IY+d),B*
ED62	SBC HL,HL	FD35 d	DEC (IY+d)	FDCB d 09	RRC (IY+d),C*
ED63 n n	LD (nn),HL	FD36 d n	LD (IY+d),n	FDCB d 0A	RRC (IY+d),D*
ED64	NEG*	FD39	ADD IY,SP	FDCB d 0B	RRC (IY+d),E*
ED65	RETN*	FD44	LD B,IYh*	FDCB d 0C	RRC (IY+d),H*
ED66	IM 0*	FD45	LD B,IYl*	FDCB d 0D	RRC (IY+d),L*
ED67	RRD	FD46 d	LD B,(IY+d)	FDCB d 0E	RRC (IY+d)
ED68	IN L,(C)	FD4C	LD C,IYh*	FDCB d 0F	RRC (IY+d),A*
ED69	OUT (C),L	FD4D	LD C,IYl*	FDCB d 10	RL (IY+d),B*
ED6A	ADC HL,HL	FD4E d	LD C,(IY+d)	FDCB d 11	RL (IY+d),C*

FDCB d 12	RL (IY+d),D*	FDCB d 5C	BIT 3,(IY+d)*	FDCB d A6	RES 4,(IY+d)
FDCB d 13	RL (IY+d),E*	FDCB d 5D	BIT 3,(IY+d)*	FDCB d A7	RES 4,(IY+d),A*
FDCB d 14	RL (IY+d),H*	FDCB d 5E	BIT 3,(IY+d)	FDCB d A8	RES 5,(IY+d),B*
FDCB d 15	RL (IY+d),L*	FDCB d 5F	BIT 3,(IY+d)*	FDCB d A9	RES 5,(IY+d),C*
FDCB d 16	RL (IY+d)	FDCB d 60	BIT 4,(IY+d)*	FDCB d AA	RES 5,(IY+d),D*
FDCB d 17	RL (IY+d),A*	FDCB d 61	BIT 4,(IY+d)*	FDCB d AB	RES 5,(IY+d),E*
FDCB d 18	RR (IY+d),B*	FDCB d 62	BIT 4,(IY+d)*	FDCB d AC	RES 5,(IY+d),H*
FDCB d 19	RR (IY+d),C*	FDCB d 63	BIT 4,(IY+d)*	FDCB d AD	RES 5,(IY+d),L*
FDCB d 1A	RR (IY+d),D*	FDCB d 64	BIT 4,(IY+d)*	FDCB d AE	RES 5,(IY+d)
FDCB d 1B	RR (IY+d),E*	FDCB d 65	BIT 4,(IY+d)*	FDCB d AF	RES 5,(IY+d),A*
FDCB d 1C	RR (IY+d),H*	FDCB d 66	BIT 4,(IY+d)	FDCB d B0	RES 6,(IY+d),B*
FDCB d 1D	RR (IY+d),L*	FDCB d 67	BIT 4,(IY+d)*	FDCB d B1	RES 6,(IY+d),C*
FDCB d 1E	RR (IY+d)	FDCB d 68	BIT 5,(IY+d)*	FDCB d B2	RES 6,(IY+d),D*
FDCB d 1F	RR (IY+d),A*	FDCB d 69	BIT 5,(IY+d)*	FDCB d B3	RES 6,(IY+d),E*
FDCB d 20	SLA (IY+d),B*	FDCB d 6A	BIT 5,(IY+d)*	FDCB d B4	RES 6,(IY+d),H*
FDCB d 21	SLA (IY+d),C*	FDCB d 6B	BIT 5,(IY+d)*	FDCB d B5	RES 6,(IY+d),L*
FDCB d 22	SLA (IY+d),D*	FDCB d 6C	BIT 5,(IY+d)*	FDCB d B6	RES 6,(IY+d)
FDCB d 23	SLA (IY+d),E*	FDCB d 6D	BIT 5,(IY+d)*	FDCB d B7	RES 6,(IY+d),A*
FDCB d 24	SLA (IY+d),H*	FDCB d 6E	BIT 5,(IY+d)	FDCB d B8	RES 7,(IY+d),B*
FDCB d 25	SLA (IY+d),L*	FDCB d 6F	BIT 5,(IY+d)*	FDCB d B9	RES 7,(IY+d),C*
FDCB d 26	SLA (IY+d)	FDCB d 70	BIT 6,(IY+d)*	FDCB d BA	RES 7,(IY+d),D*
FDCB d 27	SLA (IY+d),A*	FDCB d 71	BIT 6,(IY+d)*	FDCB d BB	RES 7,(IY+d),E*
FDCB d 28	SRA (IY+d),B*	FDCB d 72	BIT 6,(IY+d)*	FDCB d BC	RES 7,(IY+d),H*
FDCB d 29	SRA (IY+d),C*	FDCB d 73	BIT 6,(IY+d)*	FDCB d BD	RES 7,(IY+d),L*
FDCB d 2A	SRA (IY+d),D*	FDCB d 74	BIT 6,(IY+d)*	FDCB d BE	RES 7,(IY+d)
FDCB d 2B	SRA (IY+d),E*	FDCB d 75	BIT 6,(IY+d)*	FDCB d BF	RES 7,(IY+d),A*
FDCB d 2C	SRA (IY+d),H*	FDCB d 76	BIT 6,(IY+d)	FDCB d C0	SET 0,(IY+d),B*
FDCB d 2D	SRA (IY+d),L*	FDCB d 77	BIT 6,(IY+d)*	FDCB d C1	SET 0,(IY+d),C*
FDCB d 2E	SRA (IY+d)	FDCB d 78	BIT 7,(IY+d)*	FDCB d C2	SET 0,(IY+d),D*
FDCB d 2F	SRA (IY+d),A*	FDCB d 79	BIT 7,(IY+d)*	FDCB d C3	SET 0,(IY+d),E*
FDCB d 30	SLL (IY+d),B*	FDCB d 7A	BIT 7,(IY+d)*	FDCB d C4	SET 0,(IY+d),H*
FDCB d 31	SLL (IY+d),C*	FDCB d 7B	BIT 7,(IY+d)*	FDCB d C5	SET 0,(IY+d),L*
FDCB d 32	SLL (IY+d),D*	FDCB d 7C	BIT 7,(IY+d)*	FDCB d C6	SET 0,(IY+d)
FDCB d 33	SLL (IY+d),E*	FDCB d 7D	BIT 7,(IY+d)*	FDCB d C7	SET 0,(IY+d),A*
FDCB d 34	SLL (IY+d),H*	FDCB d 7E	BIT 7,(IY+d)	FDCB d C8	SET 1,(IY+d),B*
FDCB d 35	SLL (IY+d),L*	FDCB d 7F	BIT 7,(IY+d)*	FDCB d C9	SET 1,(IY+d),C*
FDCB d 36	SLL (IY+d)*	FDCB d 80	RES 0,(IY+d),B*	FDCB d CA	SET 1,(IY+d),D*
FDCB d 37	SLL (IY+d),A*	FDCB d 81	RES 0,(IY+d),C*	FDCB d CB	SET 1,(IY+d),E*
FDCB d 38	SRL (IY+d),B*	FDCB d 82	RES 0,(IY+d),D*	FDCB d CC	SET 1,(IY+d),H*
FDCB d 39	SRL (IY+d),C*	FDCB d 83	RES 0,(IY+d),E*	FDCB d CD	SET 1,(IY+d),L*
FDCB d 3A	SRL (IY+d),D*	FDCB d 84	RES 0,(IY+d),H*	FDCB d CE	SET 1,(IY+d)
FDCB d 3B	SRL (IY+d),E*	FDCB d 85	RES 0,(IY+d),L*	FDCB d CF	SET 1,(IY+d),A*
FDCB d 3C	SRL (IY+d),H*	FDCB d 86	RES 0,(IY+d)	FDCB d D0	SET 2,(IY+d),B*
FDCB d 3D	SRL (IY+d),L*	FDCB d 87	RES 0,(IY+d),A*	FDCB d D1	SET 2,(IY+d),C*
FDCB d 3E	SRL (IY+d)	FDCB d 88	RES 1,(IY+d),B*	FDCB d D2	SET 2,(IY+d),D*
FDCB d 3F	SRL (IY+d),A*	FDCB d 89	RES 1,(IY+d),C*	FDCB d D3	SET 2,(IY+d),E*
FDCB d 40	BIT 0,(IY+d)*	FDCB d 8A	RES 1,(IY+d),D*	FDCB d D4	SET 2,(IY+d),H*
FDCB d 41	BIT 0,(IY+d)*	FDCB d 8B	RES 1,(IY+d),E*	FDCB d D5	SET 2,(IY+d),L*
FDCB d 42	BIT 0,(IY+d)*	FDCB d 8C	RES 1,(IY+d),H*	FDCB d D6	SET 2,(IY+d)
FDCB d 43	BIT 0,(IY+d)*	FDCB d 8D	RES 1,(IY+d),L*	FDCB d D7	SET 2,(IY+d),A*
FDCB d 44	BIT 0,(IY+d)*	FDCB d 8E	RES 1,(IY+d)	FDCB d D8	SET 3,(IY+d),B*
FDCB d 45	BIT 0,(IY+d)*	FDCB d 8F	RES 1,(IY+d),A*	FDCB d D9	SET 3,(IY+d),C*
FDCB d 46	BIT 0,(IY+d)	FDCB d 90	RES 2,(IY+d),B*	FDCB d DA	SET 3,(IY+d),D*
FDCB d 47	BIT 0,(IY+d)*	FDCB d 91	RES 2,(IY+d),C*	FDCB d DB	SET 3,(IY+d),E*
FDCB d 48	BIT 1,(IY+d)*	FDCB d 92	RES 2,(IY+d),D*	FDCB d DC	SET 3,(IY+d),H*
FDCB d 49	BIT 1,(IY+d)*	FDCB d 93	RES 2,(IY+d),E*	FDCB d DD	SET 3,(IY+d),L*
FDCB d 4A	BIT 1,(IY+d)*	FDCB d 94	RES 2,(IY+d),H*	FDCB d DE	SET 3,(IY+d)
FDCB d 4B	BIT 1,(IY+d)*	FDCB d 95	RES 2,(IY+d),L*	FDCB d DF	SET 3,(IY+d),A*
FDCB d 4C	BIT 1,(IY+d)*	FDCB d 96	RES 2,(IY+d)	FDCB d E0	SET 4,(IY+d),B*
FDCB d 4D	BIT 1,(IY+d)*	FDCB d 97	RES 2,(IY+d),A*	FDCB d E1	SET 4,(IY+d),C*
FDCB d 4E	BIT 1,(IY+d)	FDCB d 98	RES 3,(IY+d),B*	FDCB d E2	SET 4,(IY+d),D*
FDCB d 4F	BIT 1,(IY+d)*	FDCB d 99	RES 3,(IY+d),C*	FDCB d E3	SET 4,(IY+d),E*
FDCB d 50	BIT 2,(IY+d)*	FDCB d 9A	RES 3,(IY+d),D*	FDCB d E4	SET 4,(IY+d),H*
FDCB d 51	BIT 2,(IY+d)*	FDCB d 9B	RES 3,(IY+d),E*	FDCB d E5	SET 4,(IY+d),L*
FDCB d 52	BIT 2,(IY+d)*	FDCB d 9C	RES 3,(IY+d),H*	FDCB d E6	SET 4,(IY+d)
FDCB d 53	BIT 2,(IY+d)*	FDCB d 9D	RES 3,(IY+d),L*	FDCB d E7	SET 4,(IY+d),A*
FDCB d 54	BIT 2,(IY+d)*	FDCB d 9E	RES 3,(IY+d)	FDCB d E8	SET 5,(IY+d),B*
FDCB d 55	BIT 2,(IY+d)*	FDCB d 9F	RES 3,(IY+d),A*	FDCB d E9	SET 5,(IY+d),C*
FDCB d 56	BIT 2,(IY+d)	FDCB d A0	RES 4,(IY+d),B*	FDCB d EA	SET 5,(IY+d),D*
FDCB d 57	BIT 2,(IY+d)*	FDCB d A1	RES 4,(IY+d),C*	FDCB d EB	SET 5,(IY+d),E*
FDCB d 58	BIT 3,(IY+d)*	FDCB d A2	RES 4,(IY+d),D*	FDCB d EC	SET 5,(IY+d),H*
FDCB d 59	BIT 3,(IY+d)*	FDCB d A3	RES 4,(IY+d),E*	FDCB d ED	SET 5,(IY+d),L*
FDCB d 5A	BIT 3,(IY+d)*	FDCB d A4	RES 4,(IY+d),H*	FDCB d EE	SET 5,(IY+d)
FDCB d 5B	BIT 3,(IY+d)*	FDCB d A5	RES 4,(IY+d),L*	FDCB d EF	SET 5,(IY+d),A*

```
FDCB d F0   SET 6,(IY+d),B*     FDCB d F8   SET 7,(IY+d),B*     FDE1        POP IY
FDCB d F1   SET 6,(IY+d),C*     FDCB d F9   SET 7,(IY+d),C*     FDE3        EX (SP),IY
FDCB d F2   SET 6,(IY+d),D*     FDCB d FA   SET 7,(IY+d),D*     FDE5        PUSH IY
FDCB d F3   SET 6,(IY+d),E*     FDCB d FB   SET 7,(IY+d),E*     FDE9        JP (IY)
FDCB d F4   SET 6,(IY+d),H*     FDCB d FC   SET 7,(IY+d),H*     FDF9        LD SP,IY
FDCB d F5   SET 6,(IY+d),L*     FDCB d FD   SET 7,(IY+d),L*     FE n        CP n
FDCB d F6   SET 6,(IY+d)        FDCB d FE   SET 7,(IY+d)        FF          RST 38H
FDCB d F7   SET 6,(IY+d),A*     FDCB d FF   SET 7,(IY+d),A*
```

Chapter 10

GNU Free Documentation License

Version 1.1, March 2000

Copyright © 2000 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The purpose of this License is to make a manual, textbook, or other written document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

10.1 Applicability and Definitions

This License applies to any manual or other work that contains a notice placed by the copyright holder saying it can be distributed under the terms of this

License. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you".

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (For example, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, whose contents can be viewed and edited directly and straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup has been designed to thwart or discourage subsequent modification by readers is not Transparent. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML designed for human modification. Opaque formats include PostScript, PDF, proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

10.2 Verbatim Copying

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this

License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

10.3 Copying in Quantity

If you publish printed copies of the Document numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a publicly-accessible computer-network location containing a complete Transparent copy of the Document, free of added material, which the general network-using public has access to download anonymously at no charge using public-standard network protocols. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

10.4 Modifications

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You

may use the same title as a previous version if the original publisher of that version gives permission.

- List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has less than five).
- State on the Title page the name of the publisher of the Modified Version, as the publisher.
- Preserve all the copyright notices of the Document.
- Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- Include an unaltered copy of this License.
- Preserve the section entitled "History", and its title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- In any section entitled "Acknowledgements" or "Dedications", preserve the section's title, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- Delete any section entitled "Endorsements". Such a section may not be included in the Modified Version.
- Do not retitle any existing section as "Endorsements" or to conflict in title with any Invariant Section.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties – for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

10.5 Combining Documents

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections entitled "History" in the various original documents, forming one section entitled "History"; likewise combine any sections entitled "Acknowledgements", and any sections entitled "Dedications". You must delete all sections entitled "Endorsements."

10.6 Collections of Documents

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

10.7 Aggregation With Independent Works

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, does not as a whole count as a Modified Version of the Document, provided no compilation copyright is claimed for the compilation. Such a compilation is called an "aggregate", and this License does not apply to the other self-contained works thus compiled with the Document, on account of their being thus compiled, if they are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one quarter of the entire aggregate, the Document's Cover Texts may be placed on covers that surround only the Document within the aggregate. Otherwise they must appear on covers around the whole aggregate.

10.8 Translation

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License provided that you also include the original English version of this License. In case of a disagreement between the translation and the original English version of this License, the original English version will prevail.

10.9 Termination

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10.10 Future Revisions of This License

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See http://www.gnu.org/copyleft/.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.